

## Automatic Gate Catches


### Automatic Gate Catch 50mm

Automatically latches when the gate is shut and are pad-lockable for added security. Ideal for use in light domestic applications.



### Heavy Automatic Gate Catch\* 50mm

Automatically latches when the gate is shut and are pad-lockable for added security. Ideal for use in heavy domestic, commercial and agricultural applications.



Technical Data		
Type	Standard	Heavy
Size (mm)	50	50
Bar Length (mm)	110	115
Backplate Size L x W (mm)	50 x 50	50 x 60
Catch Projection (mm)	50	60
Max. Padlock Shackle Ø (mm)	7	7
No. of Screw Holes - CSK / Pan	6	6
Screw Ø (mm)	4.0	4.0

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG - EXCLUDES FIXINGS					
AGLMBB	AGLMZB	AGLMGB	50	2	1 10
-	-	AGLHGB*	50	2	1 10
TYPE - LCB SUB TYPE - LCB03					
TIMBAG - FIXINGS INCLUDED					
AGLMBP	AGLMZP	AGLMGP	50	2	1 10
-	-	AGLHGP*	50	2	1 10
TYPE - LCP SUB TYPE - LCP03					

\* Heavy Automatic Gate Catch

## Turn Button Cast Iron NEW




Turn buttons are used for holding flush fitting doors and gates closed.

Use a 4.0 x 30mm screw to attach to door/gate

CORROSION RATINGS		Epoxy Black		Zinc		Hot Dipped Galvanised	
1	2	3	4	5	1	2	3 4 5
Occasionally damp/wet rural and sheltered areas				Urban & industrial areas with a moderate salt atmosphere			

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG - EXCLUDES FIXINGS					
TB2BB	-	TB2GB	50	2	1 600
-	TB2ZB	-	52	2.5	20 20
-	TB2ZB	-	67	2.5	20 20
TYPE - LCB SUB TYPE - LCB06					
TIMBAG - FIXINGS INCLUDED					
TB2BP	-	TB2GP	50	2	2 20
TYPE - LCP SUB TYPE - LCP06					

## Gate Spring



Gate springs provide automatic closure for single action gates. The spring tension is adjustable for increasing or decreasing the gate closing force.

### CORROSION RATINGS

Epoxy Black		Zinc	
1	2	3	4 5
Occasionally damp/wet rural and sheltered areas			

Technical Data		
Size (mm)	200	250
Spring Length (mm)	141	191
Backplate Size (mm)	30 x 30	30 x 30
No. of Screw Holes	4	4
Screw Ø (mm)	4.0	4.0

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG - EXCLUDES FIXINGS					
GS8BB	GS8ZB	200	8	1	15
GS10BB	GS10ZB	250	10	1	10
TYPE - LCB SUB TYPE - LCB04					
TIMBAG - FIXINGS INCLUDED					
GS8BP	GS8ZP	200	8	1	15
GS10BP	GS10ZP	250	10	1	10
TYPE - LCP SUB TYPE - LCP04					

## Cabin Hook Cast Iron



Ideal for retaining doors and gates in an open position in heavy domestic and agricultural applications. Made from cast iron for added strength and durability.

### CORROSION RATINGS

Epoxy Black		Zinc	
1	2	3	4 5
Occasionally damp/wet rural and sheltered areas			

Hot Dipped Galvanised		Zinc	
1	2	3	4 5
Urban & industrial areas with a moderate salt atmosphere			

Technical Data	
Size (mm)	75 - 300
Backplate Size L x W (mm)	45 x 45
No. of Screw Holes	4
Screw Ø (mm)	4.0

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS					
523467	523656	75	3	1	200
523258	523219	100	4	1	200
523963	523953	150	6	1	150
523458	523632	200	8	1	100
523957	523454	250	10	1	50
523326	523565	300	12	1	50
TIMBAG - FIXINGS INCLUDED					
527115	527568	75	3	1	10
527225	527541	100	4	1	10
527998	527114	150	6	1	10
527651	527554	200	8	1	10
527478	527665	250	10	1	10
TYPE - LCB / LCP SUB TYPE - LCP05 / LCB05					

## Kick Over Stable Latch



Kick over stable latches are ideal for stables and agricultural applications where a hands free operation is required.

Hot Dipped Galvanised		Zinc	
1	2	3	4 5
Urban & industrial areas with a moderate salt atmosphere			

Technical Data	
Size (mm)	240
Bar Length (mm)	240
Backplate Size L x W (mm)	110 x 45
Seat Brackets Size L x W (mm)	45 x 170
Seat Brackets Backplate Size L x W (mm)	45 x 80
Catch Projection (mm)	140
No. of Screw Holes - Countersunk / Pan	12
Screw Ø (mm)	5.0

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised	Zinc				
TIMBAG - FIXINGS INCLUDED					
KOSLG		240	9 ½	1	10
TYPE - FGC SUB TYPE - FGC01					

## Cabin Hook Wire Pattern



Ideal for retaining doors and gates in an open position in light domestic applications.

CORROSION RATINGS		Epoxy Black		Zinc	
1	2	3	4	5	5
Occasionally damp/wet rural and sheltered areas					

Technical Data	
Size (mm)	100 - 300
Backplate Size L x W (mm)	40 x 40
No. of Screw Holes	8
Screw Ø (mm)	4.0

Product Code		Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG - EXCLUDES FIXINGS					
WCH4BB	WCH4ZB	100	4	1	10
WCH6BB	WCH6ZB	150	6	1	10
WCH8BB	WCH8ZB	200	8	1	10
WCH10BB	WCH10ZB	250	10	1	10
WCH12BB	WCH12ZB	300	12		
TIMBAG - FIXINGS INCLUDED					
WCH4BP	WCH4ZP	100	4	1	10
WCH6BP	WCH6ZP	150	6	1	10
WCH8BP	WCH8ZP	200	8	1	10
TYPE - LCB / LCP SUB TYPE - LCB / LCP05					