

NEW

c2

EXTERIOR STRONG-FIX PREMIUM SCREW

**DESIGNED FOR
OUTDOOR APPLICATIONS**

Ideal for: Ironmongery | Decking | Fencing

**EXTREME
PULL-OUT
RESISTANCE**

**DESIGNED
FOR SUPERIOR
HOLD**

**PRECISION
PZ DRIVE
PREVENTS
"CAM-OUT"**

c2

DECK-FIX PREMIUM SCREW

**DESIGNED FOR DECKING
PLATFORMS & EXTERNAL
TIMBER CONSTRUCTION**

**DESIGNED
FOR SUPERIOR
CLAMPING WITH
HELIX TO STOP
TIMBER JACKING**

**REDUCED
IMPACT
RESISTANT
HEAD FOR A
CLEAN FINISH**

**PRECISION TX
DRIVE PREVENTS
"CAM-OUT"**

Exterior



NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above.



POZI EN 14592:2008

All the features and superior performance of the C2 screw complete with an organic plating for optimal corrosion resistance when used in the harshest of environments. Silver colour to match commonly used ironmongery. Ideal for many general external applications.

- Ribs under head for improved countersinking
- Special plating to give 1,000 hours salt spray resistance
- Multi-layer coating consisting of organic top coat barrier and a zinc base layer
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting



Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
40030C2SBX	4.0 x 30	PZ2	200	75	1800
40040C2SBX	4.0 x 40	PZ2	200	50	1200
40050C2SBX	4.0 x 50	PZ2	200	35	840
40060C2SBX	4.0 x 60	PZ2	200	15	540
40070C2SBX	4.0 x 70	PZ2	200	15	540
50040C2SBX	5.0 x 40	PZ2	200	35	840
50050C2SBX	5.0 x 50	PZ2	200	15	540
50060C2SBX	5.0 x 60	PZ2	200	16	384
50070C2SBX	5.0 x 70	PZ2	200	16	384
50080C2SBX	5.0 x 80	PZ2	200	16	384
50100C2SBX	5.0 x 100	PZ2	100	15	540
60040C2SBX	6.0 x 40	PZ3	200	15	540
60050C2SBX	6.0 x 50	PZ3	200	16	384
60070C2SBX	6.0 x 70	PZ3	200	12	288
60100C2SBX	6.0 x 100	PZ3	100	15	540

TUB (C2 IMPACT POWER BIT INCLUDED)

40030C2S	4.0 x 30	PZ2	400	12	360
40040C2S	4.0 x 40	PZ2	350	12	360
40050C2S	4.0 x 50	PZ2	300	12	360
40060C2S	4.0 x 60	PZ2	200	12	360
40070C2S	4.0 x 70	PZ2	170	12	360
50040C2S	5.0 x 40	PZ2	200	12	360
50050C2S	5.0 x 50	PZ2	180	12	360
50060C2S	5.0 x 60	PZ2	150	12	360
50070C2S	5.0 x 70	PZ2	120	12	360
50080C2S	5.0 x 80	PZ2	110	12	360
50100C2S	5.0 x 100	PZ2	80	12	360
60040C2S	6.0 x 40	PZ3	150	12	360
60050C2S	6.0 x 50	PZ3	120	12	360
60070C2S	6.0 x 70	PZ3	90	12	360
60100C2S	6.0 x 100	PZ3	60	12	360

GRAB PACK (600 PCS)

C2SGPACK	-	-	600	5	150
4.0 x 30	PZ2	140			
4.0 x 40	PZ2	100			
4.0 x 50	PZ2	70			
4.0 x 60	PZ2	60			
5.0 x 40	PZ2	80			
5.0 x 50	PZ2	55			
5.0 x 60	PZ2	45			
5.0 x 70	PZ2	30			
5.0 x 80	PZ2	20			
Impact 38mm Driver Bits	PZ2	3			



CC205

Exterior



TX DRIVE EN 14592:2008

A premium decking screw using the C2 twin-cut technology.

- Strengthened head to prevent shearing when installed with an impact tool
- Ribs under the head for improved countersinking
- Helix shank for removing debris and to improve clamping
- Coated with a patented multi-layer corrosion resistant plating to withstand 1,000 hours salt spray
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	-----------------	----------------	--------------------	--------------------

BOX (DRIVER BIT INCLUDED)

50C2D250BX	4.5 x 50	TX20	250	15	540
65C2D250BX	4.5 x 65	TX20	250	18	432
75C2D250BX	4.5 x 75	TX20	250	18	432
85C2D250BX	4.5 x 85	TX20	250	18	432

IDD04

TUB (DRIVER BIT INCLUDED)

50C2D250	4.5 x 50	TX20	250	8	288
65C2D250	4.5 x 65	TX20	250	8	288
65C2D1000	4.5 x 65	TX20	1,000	1	72
75C2D250	4.5 x 75	TX20	250	8	216

IDD04

TIMBAG

50C2DB	4.5 x 50	TX20	175	5	500
65C2DB	4.5 x 65	TX20	145	5	500
75C2DB	4.5 x 75	TX20	120	5	500

BAG01

INDUSTRY PACK (1,000 PCS)

65C2DIND	4.5 x 65	TX20	1,000	3	81
----------	----------	------	-------	---	----

IDD04

