

NEW



## FLOOR-FIX

### PREMIUM SCREW

DESIGNED FOR FIXING FLOORBOARDS TO JOISTS

Ideal for: **Hardwood** | **Softwood** | **Man-Made Board**



**DESIGNED FOR SUPERIOR HOLD**



**STOPS THE BOARDS JACKING**



**PRECISION TX DRIVE PREVENTS "CAM-OUT"**

NEW



## TONGUE-FIX

### PREMIUM SCREW

DESIGNED FOR FIXING TONGUE & GROOVE FLOORBOARDS & PANNELLING

Ideal for: **Hardwood** | **Chipboard** | **Softwood**



**DESIGNED FOR SUPERIOR HOLD**



**HIDDEN FIXING SYSTEM**



**PRECISION TX DRIVE PREVENTS "CAM-OUT"**

## Yellow






TX DRIVE EN 14592:2008




HARD & SOFT WOODS MAN MADE BOARDS

Designed for use in man-made boards such as MDF and chipboard. The C2 twin-cut tip gives rapid pick up and reduces the likelihood of splitting, whilst the steep head design with finishing teeth and self countersinking ribs ensure a flush finish.

- Specifically designed dual action head - finishing teeth and self-countersinking ribs ensures a flush finish
- Plain shank for pulling the two substrates together without manual clamping
- Coated with a high-molecular polymer lubricant that reduces the insertion torque by up to 52% and increases rust protection up to 20 times longer than a standard zinc plating
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting



NEW					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BOX (C2 IMPACT POWER BIT INCLUDED)</b>					
42055C2MDFBX	4.2 x 55	TX20	200	15	540
					CC204
<b>TUB (C2 IMPACT POWER BIT INCLUDED)</b>					
42055C2MDF	4.2 x 55	TX20	250	12	360
					CC204

## Yellow






TX DRIVE EN 14592:2008




HARD & SOFT WOODS MAN MADE BOARDS

Specially designed for attaching tongue and groove floorboards and panelling. Provides a secure hidden fixture without causing damage, allowing a flush fit with the next board.

- Reduced head for concealed countersinking
- Plain shank for pulling the two substrates together without manual clamping
- Coated with a high-molecular polymer lubricant that reduces the insertion torque by up to 52% and increases rust protection up to 20 times longer than a standard zinc plating
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting



NEW					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BOX (C2 IMPACT POWER BIT INCLUDED)</b>					
35045C2TGBX	3.5 x 45	TX10	200	50	1200
					CC203
<b>TUB (C2 IMPACT POWER BIT INCLUDED)</b>					
35045C2TG	3.5 x 45	TX10	350	20	600
					CC203