

Masonry & Concrete Screws



Rapid & Effective
Masonry & Concrete Screws



- Ideal for fitting**
- Hand rails
 - Shelf brackets
 - Security lighting
 - Metal straps banding



Non-expansion for close to edge fixing



Serrated V-threads for optimum insertion



High-low start threads for rapid pick up

Masonry Screw - Countersunk

Zinc



TX DRIVE



CONCRETE

BRICK



BLOCK

WOOD



ALL STEEL
NON-FLAMMABLE
FIXING

- Light duty fixing ideal for ironmongery handrails & brackets
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100 - 150KG

Technical Data

Substrate	Concrete $\geq 25\text{N/mm}^2$	
Length (mm)	40-80	100
Drill Hole \varnothing (mm)	5.0	5.0
Min. Embedment Depth (mm)	25	37
Min. Drill Hole Depth (mm)	35	47
Rec. Tensile Load (kN)	1.00	1.50
Max Rec. Load (kg)	100	150

Product Code	Size (mm)	Driver Bit Size	Max. Fixture Thickness (mm)	Fixture Clearance Hole \varnothing (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)							
640MFCSK	6.0 x 40	TX25	15	6.5	100	18	648
660MFCSK	6.0 x 60	TX25	35	6.5	100	12	432
680MFCSK	6.0 x 80	TX25	55	6.5	100	12	432
6100MFCSK	6.0 x 100	TX25	63	6.5	100	10	360

TIMPAC


725157	6.0 x 40	TX25	15	6.5	12	10	-
725375	6.0 x 60	TX25	35	6.5	10	10	-
725010	6.0 x 80	TX25	55	6.5	8	10	-
725863	6.0 x 100	TX25	63	6.5	6	10	-

Masonry Screw - Pan Head

Zinc



TX DRIVE



CONCRETE

BRICK



BLOCK

WOOD



ALL STEEL
NON-FLAMMABLE
FIXING

- Light duty fixing ideal for ironmongery
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100 - 150KG

Technical Data

Substrate	Concrete $\geq 25\text{N/mm}^2$	
Length (mm)	40-80	100
Drill Hole \varnothing (mm)	5.0	5.0
Min. Embedment Depth (mm)	25	37
Min. Drill Hole Depth (mm)	35	47
Rec. Tensile Load (kN)	1.00	1.50
Max Rec. Load (kg)	100	150

Product Code	Size (mm)	Driver Bit Size	Max. Fixture Thickness (mm)	Fixture Clearance Hole \varnothing (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)							
640MFPAN	6.0 x 40	TX25	15	6.5	100	18	648
660MFPAN	6.0 x 60	TX25	35	6.5	100	12	432
680MFPAN	6.0 x 80	TX25	55	6.5	100	12	576
6100MFPAN	6.0 x 100	TX25	63	6.5	100	10	360

TIMPAC

725500	6.0 x 40	TX25	15	6.5	12	10	-
725997	6.0 x 60	TX25	35	6.5	10	10	-