

Cramps & Ties



Safety Frame Cramp



| Product Code | Width (mm) | Projection (mm) | Upstand (mm) | Qty (pcs) | Break (packs) | | | |
|-------------------------|---------------|-----------------|-----------------|--------------|------------------|--|--|--|
| | | BOX | | | | | | |
| Stainless Steel - 2.0mm | | | | | | | | |
| 100SFCS | 19 | 100 | 50 | 250 | 10 | | | |
| 150SFCS | 19 | 150 | 50 | 250 | 10 | | | |
| 2008ECS | 10 | 200 | 50 | 250 | 10 | | | |

Heavy Duty Fishtailed Cramp



| Product Code | Width (mm) | Projection (mm) | Upstand (mm) | Qty (pcs) | Break (pcs) | | | |
|--------------------------|---------------|-----------------|-----------------|--------------|----------------|--|--|--|
| | | BAG | | | | | | |
| Galvanised Steel - 2.3mm | | | | | | | | |
| 100FFC | 25 | 100 | 50 | 25 | 100 | | | |
| 150FFC | 25 | 150 | 50 | 25 | 100 | | | |
| 200FFC | 25 | 200 | 50 | 25 | 100 | | | |
| | | | | | DEMMA | | | |

Window Board Tie



| | | Projection (mm) | | | | | | |
|--------------------------|----|--------------------|-----|----|--|--|--|--|
| вох | | | | | | | | |
| Galvanised Steel - 2.0mm | | | | | | | | |
| MIDTAG | 40 | 4.47 | 0.5 | 40 | | | | |

| BOX | | | | | | |
|--------------------------|----|-----|----|----|-----|------------|
| Galvanised Steel - 2.0mm | | | | | | |
| WBT10 | 12 | 147 | 25 | 10 | - | 50 |
| WBT | 12 | 147 | 25 | 1 | 100 | - BMW10 |

Movement Ties

NEW

When used with debonding sleeves, provide restraint in one direction and horizontal movement for expansion and contraction found in long spans of brickwork. The tie sits inside the debonding sleeve allowing the tie to move in situ.



Qty

MOO Otv




Movement Tie Debonding Sleeves

NEW

Pack MOQ Qty

Designed for use with movement ties to provide restraint in one direction and horizontal movement for expansion and contraction found in long spans of brickwork. The debonding sleeve is located over the tie to allow the tie to move.



Timber Frame Tie

Timber Frame Ties are suitable for tying masonry outer cladding to softwood structural framework of domestic dwellings and industrial/commercial buildings up to 4 storeys and not greater than 15m in height.



- Complies with a DD140 Type 6 tie.
- Meets with the appropriate parts of NHBC standards.
- Supplied with annular rings hank nails.

| Code | (mm) | (mm) | (mm) | (pcs) | (packs) | | | |
|-----------------|------|------|------|-------|---------|--|--|--|
| BOX | | | | | | | | |
| Stainless Steel | | | | | | | | |
| 269413 | 19 | 130 | 50 | 250 | 10 | | | |
| 269846 | 19 | 155 | 75 | 250 | 10 | | | |
| 269719 | 19 | 180 | 100 | 250 | 10 | | | |
| | | | | | BMW10 | | | |

Screw-in Frame Tie



| Product Code | Length (mm) | Thread Length (mm) | Thread Dia (mm) | Pack Qty (pcs) | Qty Break (packs) | | | | |
|-----------------|----------------|--------------------------|-----------------------|----------------------|-------------------------|--|--|--|--|
| BOX | | | | | | | | | |
| Zinc & Yellow | | | | | | | | | |
| 150SFT | 150 | 40 | 6 | 100 | 4 BMW10 | | | | |