

Cavity Wall Ties

Perfect for masonry cavity walls in domestic houses and small commercial buildings of up to three storeys and maximum 15m in height. Manufactured from A2 Stainless Steel for ultimate corrosion resistance.

Type 2 - General Duty Wall Ties



Product Code	Length x Gauge (mm)	Cavity Width (mm)	Max. Wall Height (m)	Pack Qty (pcs)	Qty Break (packs)
BUNDLE					
A2 Stainless Steel					
225WT2	225 x 3	76 to 100	15	250	10
250WT2	250 x 3	101 to 125	15	250	10
275WT2	275 x 3	Up to 150	15	250	10

BMW10

Type 4 - Light Duty Wall Ties



Product Code	Length x Gauge (mm)	Cavity Width (mm)	Max. Wall Height (m)	Pack Qty (pcs)	Qty Break (packs)
BUNDLE					
A2 Stainless Steel					
200WT4	200 x 2.3	50 to 75	10	250	10
225WT4	225 x 2.3	76 to 100	10	250	10
250WT4	250 x 2.7	101 to 125	10	250	10
275WT4	275 x 2.7	up to 150	10	250	10

BMW10



Insulation Retaining Discs

Used with a cavity wall tie to hold insulation material against the inner wall of the cavity.



Product Code	Diameter (mm)	Colour	Pack Qty (pcs)	Qty Break (packs)
BAG				
LOCIRD65BL	65	Black	250	6
LOCIRD80R	80	Red	250	4

BMW10

Damp Proofing

Damp Proof Membrane



Handy Pack

Commonly used to protect a building's concrete slab from moisture rising from the foundations. A damp proof membrane or DPM is a versatile product and can also be used for a wide range of applications such as creating a protective surface before laying laminate or wood floors. BBA certified.

- Membrane made from 100% recycled materials
- EN 13967:2012

Product Code	Size (m)	Thickness (Microns)	Thickness (Gauge)	Pack Qty (pcs)	Qty Break (packs)
ROLL					
887125	4 x 12.5	500	2000	1	10
887025	4 x 25.0	250	1000	1	10
887425	4 x 25.0	300	1200	1	10

TTS01

TTS01

Damp Proof Course



Damp proof course or DPC offers a protective barrier and is used within the inner layers of brick or block walls to protect buildings from rising damp.

- 100% recycled materials

Product Code	W (mm)	L (m)	Thickness (Microns)	Thickness (Gauge)	Pack Qty (pcs)	MOQ Qty (packs)
ROLL						
887100	100	30	500	2000	1	9
887112	112	30	500	2000	1	8
887150	150	30	500	2000	1	6
887225	225	30	500	2000	1	4
887300	300	30	500	2000	1	3
887450	450	30	500	2000	1	2
887600	600	30	500	2000	1	2

TTS02

Double Sided Damp Proof Membrane Jointing Tape

A high performance double sided butyl tape used for bonding DPMs. Use with High Strength PVC Builders Tape to provide a continuous damp proof seal between two sheets, where joints cannot be avoided.



- High adhesion
- Backing paper for easy application

Product Code	Colour	Length (m)	Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
ROLL					
DSDJT	Black	10	50	1	12

TAP11

High Strength PVC Builders Tape

A strong versatile PVC tape used for jointing PVC and polythene sheets and membranes. Frequently used for sealing contamination barriers, polythene dust sheets, silage covers and bales.



- Flame retardant
- Perfect for electrical, patching & jointing applications

Product Code	Colour	Length (m)	Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
ROLL					
HSBT	Black	33	75	1	36

TAP08

Full Tape Range

See Page 186