

Plain Bearing Flush Hinge

Ideal for hanging light cupboard and cabinet doors in quality joinery projects.

- Flush finish enables a quick and easy fitting with no morticing required
- · Brass bearing to prevent wear and provide a lifetime of silent, smooth door operation
- · Manufactured from high quality extruded brass to guarantee no rust and a superior finish
- Avaliable in a variety of finishes

Size LxW (mm)

Thickness (mm)

Knuckle Ø (mm)

Screw Size (mm)

Rec. Screw Ø (mm)

Rec. Screw Gauge (Imp.)











Polished Chrome

Satin Chrome

Product Code

Technical Data

60 x 41

1.40

6.0

3.0 x 15

3.0

Polished Brass	Antique Brass	Bronze	Polished Chrome	Satin Chrome	LxW (mm)	Qty (pair)	Qty (packs)			
BAG - FIXINGS INCLUDED										
234077	234579	234862	234606	234432	60 x 41	1	100			
234316	234685	234111	234553	234797	75 x 50	1	100			
							RDH07			

75 x 50

1.70

64

3.5 x 25

3.5

6

Hurlinge - Fixed Pin (104)

Ideal for use in a variety of joinery applications. Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

- · Offset knuckle provides an even appearance between the door and frame
- · Flush finish enables a quick and easy fitting with no morticing required
- · Lugs on the knuckle for quick and simple alignment
- · Manufactured from steel and available in a variety of finishes



Technical Data						
Size L x W (mm)	75 x 55	101 x 66				
Thickness (mm)	1.5	2.0				
Knuckle Ø (mm)	8.0	9.0				
Rec. Screw Ø (mm)	3.5	4.0				
Rec. Screw Gauge (Imp.)	6	8				
Max. Door Weight (kg)	20	30				





Polished Brass Chrome

Product Code

Zinc	Electro Brass	Polished Chrome	LxW (mm)	Pack Qty (pair)	Carton Qty (packs)		
BAG - EXCLUDES FIXINGS							
434457	434367	434202	75 x 55	1	90		
434142	434819	434666	101 x 66	1	60		

Flush Hinge (105)

Ideal for use in a variety of joinery applications. Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

- $\bullet\,$ Flush finish enables a quick and easy fitting with no morticing required
- Manufactured from steel and available in a variety of finishes



Technical Data								
Size L x W (mm)	38 x 28	50 x 38.5	63 x 37	75 x 51				
Thickness (mm)	1.2	1.2	1.2	1.5				
Knuckle Ø (mm)	6.5	6.5	6.5	8.0				
Rec. Screw Ø (mm)	3.5	3.5	3.5	3.5				
Rec. Screw Gauge (Imp.)	6	6	6	6				
Max. Door Weight (kg)	2	5	10	12				





Zinc	Electro Brass	White	LxW (mm)	Pack Qty (pair)	Carton Qty (packs)
		TIM	PAC - FIXINGS INCLUDED		
434451P	434464P	-	38 x 28	1	10
434056P	434872P	434915P	50 x 38.5	1	10
434900P	434946P	-	63 x 37	1	10
434777P	434174P	-	75 x 51	1	10
		BA	AG - EXCLUDES FIXINGS		
434451	434464	-	38 x 28	1	200
434056	434872	434915	50 x 38.5	1	200
434900	434946	-	63 x 37	1	90
434777	434174	-	75 x 51	1	90 IDH07

Hurlinge - Loose Pin (104Z)

Ideal for use in a variety of joinery applications. Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

- · Offset knuckle provides an even appearance between the door and frame
- Loose pin for easy door removal
- Flush finish enables a quick and easy fitting with no morticing required
- Lugs on the knuckle for quick and simple alignment
- Manufactured from steel and available in a variety of finishes



Technical Data						
Size LxW (mm)	75 x 52	100 x 66				
Thickness (mm)	1.5	2.0				
Knuckle Ø (mm)	8.0	9.0				
Rec. Screw Ø (mm)	3.5	4.0				
Rec. Screw Gauge (Imp.)	6	8				
Max. Door Weight (kg)	20	30				





Brass

Chrome

Product	Code

Zinc	Electro Brass	Polished Chrome	LxW (mm)	Qty (pair)	Qty (packs)			
	TIMPAC - FIXINGS INCLUDED							
434432P	434728P	-	100 x 66	1	10			
BAG - EXCLUDES FIXINGS								
434002	434976	434641	75 x 52	1	90			
434432	434728	434258	100 x 66	1	60			
					IDH05			