

Cane Bolt



Ideal for lightweight gates, garages and shed doors in light domestic applications. Supplied with socket bolt keep.

Technical Data	
Bolt Length (mm)	300
Bolt Ø (mm)	12
Plate Size L x W (mm)	75 x 40
Socket Keep Size Ø (mm)	16
No. of Screw Holes	4
Screw Ø (mm)	4.0

Product Code	Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black				
BAG - EXCLUDES FIXINGS				
282159	300	12	1	10
				BTB08

TIMBAG - FIXINGS INCLUDED				
287254	300	12	1	10
				BTPO7

Garage Drop Down Bolt



Ideal for securing the bottom of gates and doors in domestic and industrial applications. Extended bolt length for ease of operation and an adjustable bolt throw by moving the keep position.

Technical Data				
Bolt Length (mm)	300	450		
Bolt Ø (mm)	14	14		
Handle Plate Size L x W (mm)	45 x 88	45 x 88		
Keep Plate Size L x W (mm)	45 x 64	45 x 64		
Flat Plate Size L x W (mm)	60 x 29	60 x 29		
Flat Keep Hole Ø (mm)	20	20		
Socket Keep Size Ø x L (mm)	19 x 50	19 x 50		
No. of Screw Holes	16	20		
Screw Ø (mm)	4.0	4.0		

Product Code	Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black				
Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS				
DDB12BB	DDB12GB	300	12	1
				20
DDB18BB	DDB18GB	450	18	1
				16
				BTB08

TIMBAG - FIXINGS INCLUDED				
DDB12BP	DDB12GP	300	12	1
				15
DDB18BP	DDB18GP	450	18	1
				15
				BTPO7

Heavy Locking Drop Down Bolt



Ideal for securing the bottom of gates and doors in commercial and industrial applications. The bolts are padlockable and fixed with carriage bolts for added security. Extended bolt length for ease of operation and an adjustable bolt throw by moving the keep position.

Technical Data	
Bolt Length (mm)	450
Bolt Ø (mm)	14
Plate Size L x W (mm)	95 x 64
Flat Keep Size L x W (mm)	45 x 64
Flat Plate Size L x W (mm)	60 x 29
Flat Keep Hole Ø (mm)	20
Socket Keep Size Ø x L (mm)	19 x 50
Staple Keep Plate Size L x W (mm)	50 x 50
Max. Padlock Shackle Ø (mm)	16
No. of Carriage Bolt Holes	4
Carriage Bolt Ø (mm)	M6
No. of Screw Holes	16
Screw Ø (mm)	4.0

Product Code	Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black				
Hot Dipped Galvanised				
TIMBAG - FIXINGS INCLUDED				
LDDB18GP	450	18	1	10
				BTPO7

Garage Door Holders

Junior Garage Door Holder Wide Lintel 375mm



523114

For holding garage and barn doors in an open position. Angle of opening can be varied by adjusting the distance of the lintel bracket from the hinge edge. Automatically engages when the door is opened and released by pulling the cord. Ideal for applications where the door cannot be propped open or hands free operation is needed.

- Mounts to the underside of the lintel and requires minimum lintel width of 60mm
- For doors below 900mm wide

Product Code	Type	Lintel Type	Size (mm)	Size (inch)	Pack Qty (pcs)	Carton Qty (packs)
BAG - EXCLUDES FIXINGS						
523114	Junior	Wide	375	15	1	20
523417	Senior	Wide	600	24	1	20
523998	Senior	Narrow	600	24	1	20
						GAB07

Senior Garage Door Holder Wide Lintel 600mm



523417

For holding garage and barn doors in an open position. Angle of opening can be varied by adjusting the distance of the lintel bracket from the hinge edge. Automatically engages when the door is opened and released by pulling the cord. Ideal for applications where the door cannot be propped open or hands free operation is needed.

- Mounts to the underside of the lintel and requires minimum lintel width of 60mm
- For doors over 900mm wide

Senior Garage Door Holder Narrow Lintel 600mm



523998

For holding garage and barn doors in an open position. Angle of opening can be varied by adjusting the distance of the lintel bracket from the hinge edge. Automatically engages when the door is opened and released by pulling the cord. Ideal for applications where the door cannot be propped open or hands free operation is needed.

- Mounts to the side of the lintel and requires minimum lintel width of 60mm
- For doors over 900mm wide

Technical Data			
Product Code	523114	523417	523998
Size (mm)	375	600	600
To Suit Lintel Type	Wide	Wide	Narrow
Lintel Fixing Plate Size W x L (mm)	45 x 80	45 x 80	44 x 58
Door Fixing Plate Size L x W (mm)	58 x 21	47 x 58	47 x 58
Cord Length (mm)	1020	1020	660
No. of Screw Holes	8	8	8
Screw Ø (mm)	4.0	4.0	4.0