



Strong Tee Hinge



Ideal for heavy weight high use gates, sheds and garage doors in domestic applications.

Technical Data

Band Length (mm)	250	300	350	400	450	600
Band Thickness (mm)	2.3	2.3	2.3	2.8	2.8	2.8
Knuckle Ø (mm)	12.0	12.0	12.0	14.0	14.0	14.0
Leaf Size L x W (mm)	100 x 20	115 x 30	127 x 30	140 x 30	150 x 30	166 x 40
Max. Gate Weight (kg)	40	40	60	60	80	80
No. of Screw Holes (Pair)	14	18	18	18	18	20
Screw Ø (mm)	4.0	4.0	4.0	4.0	5.0	5.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
BAG						
STH10BB	STH10GB	250	10	500 - 750	1 Pair	40 Pairs
STH12BB	STH12GB	300	12	600 - 900	1 Pair	30 Pairs
STH14BB	STH14GB	350	14	700 - 1050	1 Pair	20 Pairs
STH16BB	STH16GB	400	16	800 - 1200	1 Pair	20 Pairs
STH18BB	STH18GB	450	18	900 - 1350	1 Pair	20 Pairs
STH24BB	STH24GB	600	24	1200 - 1800	1 Pair	10 Pairs

HGB03

TIMBAG - FIXINGS INCLUDED

STH10B	STH10G	250	10	500 - 750	1 Pair	6 Pairs
STH12B	STH12G	300	12	600 - 900	1 Pair	6 Pairs
STH14B	STH14G	350	14	700 - 1050	1 Pair	6 Pairs
STH16B	STH16G	400	16	800 - 1200	1 Pair	8 Pairs
STH18B	STH18G	450	18	900 - 1350	1 Pair	6 Pairs
STH24B	STH24G	600	24	1200 - 1800	1 Pair	4 Pairs

HGP03

Scotch Tee Hinge



Ideal for heavy weight high use gates and shed doors in domestic, commercial and agricultural applications.

Technical Data

Band Length (mm)	100	150	200	250	300	355	400	450	500	600
Thickness (mm)	2.2	2.2	2.2	2.2	2.8	3.0	3.0	3.0	3.0	3.0
Knuckle Ø (mm)	11	12	12	12	12	16	16	16	16	16
Leaf Size L (mm)	90	90	100	100	145	145	175	175	175	175
Leaf Size W (mm)	30	30	30	30	40	40	55	55	55	55
Max. Gate Weight (kg)	10	25	40	50	60	80	80	100	100	100
No. of Screw Holes (Pair)	12	12	12	12	12	16	16	16	16	16
Screw Ø (mm)	4.0	4.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised						
BAG						
442270		100	4	200 - 300	1 Pair	50 Pairs
442159		150	6	300 - 450	1 Pair	50 Pairs
442241		200	8	400 - 600	1 Pair	40 Pairs
442657		250	10	500 - 750	1 Pair	30 Pairs
442225		300	12	600 - 900	1 Pair	25 Pairs
442678		350	14	700 - 1050	1 Pair	10 Pairs
442336		400	16	800 - 1200	1 Pair	10 Pairs
442784		450	18	900 - 1350	1 Pair	10 Pairs
442114		500	20	1000 - 1500	1 Pair	8 Pairs
442878		600	24	1200 - 1800	1 Pair	8 Pairs

HGB04

TIMBAG - FIXINGS INCLUDED

447558	100	4	200 - 300	1 Pair	10 Pairs
447254	150	6	300 - 450	1 Pair	10 Pairs
447232	200	8	400 - 600	1 Pair	10 Pairs
447778	250	10	500 - 750	1 Pair	10 Pairs
447669	300	12	600 - 900	1 Pair	10 Pairs
447552	350	14	700 - 1050	1 Pair	8 Pairs
447154	400	16	800 - 1200	1 Pair	8 Pairs
447785	450	18	900 - 1350	1 Pair	4 Pairs
447336	500	20	1000 - 1500	1 Pair	4 Pairs
447123	600	24	1200 - 1800	1 Pair	4 Pairs

HGP04

Medium Strap Hinge



Commonly used for bi-folding garage and shed doors in domestic applications.



Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Technical Data

Band Length (mm)	150	200
Thickness (mm)	2.0	2.0
Overall Length (mm)	300	400
Knuckle Ø (mm)	10.0	10.0
To Suit Gate Width (mm)	300 - 450	400 - 600
Max. Gate Weight (kg)	20	20
No. of Screw Holes (Pair)	12	16
Screw Ø (mm)	4.0	4.0

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Zinc					
BAG					
SH6ZB		150	6	1 Pair	60 Pairs
SH8ZB		200	8	1 Pair	60 Pairs

HGB05