

Heavy Reversible Hinge



Heavy reversible hinges are ideal for flush mounted heavy gates, garage and stable doors in domestic, commercial and agricultural applications. The pins of the hinges mount into the hinge cups and prevent gates or doors from being lifted off.

Technical Data											
Band Length (mm)	250	300	350	400	450	500	600	750	900	1050	1200
Band Thickness (mm)	4.8	4.8	4.8	4.8	4.8	4.8	5.6	5.6	5.6	5.6	5.6
Band Width (mm)	40	40	40	40	50	50	50	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	16	19	19	19	19
Pin Ø (inch)	½	½	½	½	¾	¾	¾	¾	¾	¾	¾
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	22	22	22	26	26	26	26	30	30	30	30
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
TIMBAG - FIXINGS INCLUDED						
HRH250B	HRH250G	250	10	500 - 750	1 Pair	5 Pairs
HRH300B	HRH300G	300	12	600 - 900	1 Pair	5 Pairs
HRH350B	HRH350G	350	14	700 - 1050	1 Pair	5 Pairs
HRH400B	HRH400G	400	16	800 - 1200	1 Pair	5 Pairs
HRH450B	HRH450G	450	18	900 - 1350	1 Pair	5 Pairs
HRH500B	HRH500G	500	20	1000 - 1500	1 Pair	5 Pairs
HRH600B	HRH600G	600	24	1200 - 1800	1 Pair	5 Pairs
HRH750B	HRH750G	750	30	1500 - 2250	1 Pair	5 Pairs
HRH900B	HRH900G	900	36	1800 - 2700	1 Pair	5 Pairs
HRH1050B	HRH1050G	1050	42	2100 - 3150	1 Pair	2 Pairs
HRH1200B	HRH1200G	1200	48	2400 - 3600	1 Pair	2 Pairs

FGP02

Adjustable Band & Hook on Plate



Adjustable hook and band hinges are for hanging doors or gates flush with the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic, commercial and agricultural applications. They feature an adjustable eye bolt to allow for gate alignment whilst being fitted or at a later stage if any movement occurs.

Technical Data						
Band Length (mm)	350	450	600	750	900	1200
Band Thickness (mm)	5.0	5.0	5.0	5.0	5.0	5.0
Band Width (mm)	50	50	50	60	60	70
Pin Ø (mm)	19	19	19	19	19	19
Pin Ø (inch)	¾	¾	¾	¾	¾	¾
Hook Plate L x W (mm)	160 x 50	160 x 50	200 x 60	200 x 60	200 x 60	200 x 60
No. of Bolt Holes (Pair)	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	14	14	14	18	20
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
TIMBAG - FIXINGS INCLUDED						
ABH350B	ABH350G	350	14	700 - 1050	1 Pair	4 Pairs
ABH450B	ABH450G	450	18	600 - 900	1 Pair	4 Pairs
ABH600B	ABH600G	600	24	1200 - 1800	1 Pair	4 Pairs
ABH750B	ABH750G	750	30	1500 - 2250	1 Pair	4 Pairs
ABH900B	ABH900G	900	36	1800 - 2700	1 Pair	4 Pairs
ABH1200B	ABH1200G	1200	48	2400 - 3600	1 Pair	2 Pairs

FGH02

Hook on Rectangular Plate



Spare hook on plate for hook and band hinges.

Technical Data			
Pin Ø (mm)	12	16	19
Pin Ø (inch)	½	¾	¾
No. of Screw Holes (Pair)	8	8	8
Screw Ø (mm)	6.0	6.0	6.0

Product Code		Pin Ø (mm)	Pin Ø (inch)	Hook Plate L x W (mm)	To Suit Band Size (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised							
TIMBAG - FIXINGS INCLUDED							
HRP12G		12	½	115 x 40	250 - 400	1 Pair	20 Pairs
HRP16G		16	¾	160 x 50	450 - 600	1 Pair	20 Pairs
HRP19G		19	¾	200 x 75	750 - 900	1 Pair	10 Pairs

FGH04

Gate Hooks to Build



Gate hooks to build are used for embedding in between layers of the post brickwork and can be used with straight and cranked hook and band hinges.

Product Code		Pin Ø (mm)	Pin Ø (inch)	Length (mm)	To Suit Brickwork	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised							
TIMBAG - FIXINGS INCLUDED							
GHBSB12G		12	½	60	Single	250 - 400	1 Pair 10 Pairs
GHBDB12G		12	½	180	Double	250 - 400	1 Pair 10 Pairs
GHBSB16G		16	¾	65	Single	450 - 600	1 Pair 10 Pairs
GHBDB16G		16	¾	180	Double	450 - 600	1 Pair 10 Pairs
GHBSB19G		19	¾	65	Single	750 - 900	1 Pair 10 Pairs
GHBDB19G		19	¾	180	Double	750 - 900	1 Pair 10 Pairs

FGH04