## rimea

## **Straight Barrel Bolt**

Ideal for securing flush fitting doors in a closed position.



BAG - EXCLUDES FIXINGS									
200945	200225	200856	75 x 25	15	1	10			
200328	200943	200379	100 x 25	20	1	10			
200496	200114	200164	150 x 25	22	1	10			
TIMPAC - FIXINGS INCLUDED									
200945P	200225P	200856P	75 x 25	15	1	10			
200328P	200943P	200379P	100 x 25	20	1	10			
200496P	200114P	200164P	150 x 25	22	1	10			
						BSA02			

## **Necked Barrel Bolt**

Necked barrel bolts are used for securing recessed fitted doors in a closed position.



200200 200555 200645 150 x 25 20 1 10 TIMPAC - FIX NGS INCLUDED 200764F 200694P 200367P 75 x 25 12 1 10 200321P 200996P 200158P 100 x 25 16 10 200200P 200555P 200645P 150 x 25 20 1 10 RSA02

Ideal for securing flush fitting doors in a closed position.

- Made from satin anodised aluminium
- Face fixing Internal use only

Qty



Product Code	0:	Pack Qty (pack)	Carton Qty (packs)						
Satin Anodised Aluminium	Size L x W (mm)								
BAG - FIXINGS INCLUDED									
725204BX	50 x 25	1	10						
725205BX	75×25	1	10						
725217BX	100 x 25	1	10						
TIMPAC - FIXINGS INCLUDED									
725204	50 x 25	1	5						
725205	75×25	1	5						
725217	100 x 25	1	5 BSA02						

Necked barrel bolts are used for securing recessed fitted doors in a closed position.

- Made from satin anodised aluminium
- Face fixing Internal use only



Product Code	Size	Pack Qty (pack)	Carton						
Satin Anodised Aluminium	LxW (mm)		Qty (packs)						
BAG - FIXINGS INCLUDED									
725224BX	75x25	1	10						
TIMPAC - FIXINGS INCLUDED									
725224	75x25	1	5 BSA02						

## **Lever Action Flush Bolt**

Lever action flush bolts are morticed into the face or leading edge of the door providing a flush door surface finish. They are commonly fitted to double doors to secure the slave door leaf in place

Made from solid brass



Satin Chrome



Chrome Polished

Polished





Lever action flush bolts are morticed into the face or leading edge of the door providing a flush finish. Commonly fitted to internal double doors to secure the slave door leaf in place.

 Made from satin anodised aluminium Flush fitting Internal use only

