rimeo

Flush Hinge (105)

Ideal for use in a variety of joinery applications. Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

· Flush finish enables a quick and easy fitting with no morticing required



Technical Data							
Size L x W (mm)			38 x 2	28	50 x 38.5	63 x 37	75 x 51
Thickness	(mm)		1.2		1.2	1.2	1.5
Knuckle Ø	(mm)		6.5		6.5	6.5	8.0
Rec. Screw	/Ø(mm)		3.5		3.5	3.5	3.5
Rec. Screw	Rec. Screw Gauge (Imp.)				6	6	6
Max. Door	Weight (kg)		2		5	10	12
Zinc	Electro Brass	W	nite		LxW (mm)	Pack Qty (pair)	Carton Qty (packs)
	BAG - E	XCI	UDE	ES	FIXING	SS	
434451	434464		-		38 x 28	1	200
434056	434872	434	915	5	0 x 38.5	1	200
434900	434946		-		63 x 37	1	90
434777	434174		-		75 x 51	1	90
TIMPAC - FIXINGS INCLUDED							
434451P	434464P		-		38 x 28	1	10

50 x 38.5

63 x 37

75 x 51

10

10 1

IDH07

10

1

Hurlinge - Fixed Pin (104)

Ideal for use in a variety of joinery applications. Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

- Offset knuckle provides an even appearance between the door and frame
- Flush finish enables a quick and easy fitting with no morticing required
- Lugs on the knuckle for guick and simple alignment





Electro Brass Chrome


Technical Data						
Size L x W (mm)	75 x 55	101 x 66				
Thickness (mm)	1.5	2.0				
Knuckle Ø (mm)	8.0	9.0				
Rec. Screw Ø (mm)	3.5	4.0				
Rec. Screw Gauge (Imp.)	6	8				
Max. Door Weight (kg)	20	30				

P		Pack	Carton				
Zinc	Electro Brass	Polished Chrome	LxW (mm)	W Qty	Qty		
BAG - EXCLUDES FIXINGS							
434457	434367	434202	75 x 55	1	90		
434142	434819	434666	101 x 66	1	60		
					IDH04		

Hurlinge - Loose Pin (104Z)

Ideal for use in a variety of joinery applications Commonly used for light cupboards, cabinets, bifold, louvre doors and shutters.

- Loose pin for easy door removal
- Offset knuckle provides an even appearance between the door and frame



and simple alignment



Zinc



lectro	Po
Brass	Cł

Chroi	me
	Technical Data

Size L x W	(mm)		75 x 52	100 x 66	
Thickness	(mm)		1.5	2.0	
Knuckle Ø	(mm)			8.0	9.0
Rec. Scree	wØ(mm)			3.5	4.0
Rec. Screw Gauge (Imp.)					8
Max. Door Weight (kg)				20	30
Zinc	Product Co Electro Brass	de Polished Chrome	LxW (mm)	Pack Qty (pair)	Carton Qty (packs)
	BAG -	EXCLUDE	S FIXI	NGS	
434002	434976	434641	75 x 52	. 1	90
434432	434728	434258	100 x 6	61	60
	TIMPAC	- FIXINGS	S INCLU	JDED	
434432P	434728P	-	100 x 6	61	10
					IDH05

Specialist Hinges

434872P 434915P

Rising Butt Hinge (466)

Designed for uneven floor surfaces or obstructions such as deep pile carpets.

- Spiral knuckle lifts the door throughout the opening cycle
- · Quick and easy removal of doors
- Self-closing design

434056P

434777P

434900P 434946P

434174P

• Manufactured from steel and available in zinc and electro brass finishes



Technical Data		Right Hand	59	
Size L x W (mm)	75 x 72	100 x 86		
Thickness (mm)	2.5	3.0	Right	· · · · · ·
Knuckle Ø (mm)	14.0	15.5	rugin	8 1 8
Rec. Screw Ø (mm)	4.0	5.0		U U
Rec. Screw Gauge (Imp.)	8	10		
Max. Door Weight (kg)	30	40		8

Product Code

Zinc Left Hand	Zinc Right Hand		Electro Brass Right Hand	LxW (mm)	Pack Qty (pair)	Carton Qty (packs)
		BAG -	EXCLUDES	FIXINGS		
434910	434349	434483	434639	75 x 72	1	30
434157	434792	434458	434127	100 x 86	1	20
		TIMPAC	- FIXINGS I	NCLUDED		
434910P	434349P	-	-	75 x 72	1	30
						IDH06

Lift Off Hinge (457)

Designed to enable the door to be lifted out of the frame

- · For doors that may require
- emergency access when closed
- · Quick and easy removal of doors Manufactured from steel
- in a zinc finish



Technical Data						
Size L x W (mm)	75 x 62	101 x 63				
Thickness (mm)	2.0	3.0				
KnuckleØ(mm)	10.3	13				
Rec. Screw Ø (mm)	4.0	5.0				
Rec. Screw Gauge (Imp.)	8	10				
Max. Door Weight (kg)	20	30				



Product Code			Pack	Carton			
Zinc Left Hand	Zinc Right Hand	LxW (mm)	Qty (pair)	Qty (packs)			
	BAG - EXCLUDES FIXINGS						
434706	434467	75×62	1	50			
434815	434307	101 x 63	1	30			
				IDH15			