TIMCO

Bolts

Brenton Padbolt

Brenton padbolts are used for securing flush mounted gates and shed doors in domestic and light commercial applications. They are pad-lockable and fixed with carriage bolts for added security.

Technical Data				
Bolt Length (mm)	102	100	150	200
Bolt Ø (mm)	12	12	12	12
Bolt Throw (mm)	12	30	45	45
Plate Size (mm)	120 x 45	130 x 45	180 x 45	225 x 45
Staple Keep Size L x W (mm)	83 x 23	56 x 33	56 x 33	56 x 33
Max. Padlock Shackle Ø (mm)	10	10	10	10
No. of Carriage Bolt Holes	4	4	4	4
Carriage Bolt Ø (mm)	M6	M6	M6	M6
No. of Screw Holes	6	6	6	6
Screw Ø (mm)	4.0	4.0	4.0	4.0

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS						
BP4BB	BP4ZB	BP4GB	100	4	1	80
BP6BB	BP6ZB	BP6GB	150	6	1	60
BP8BB	BP8ZB	BP8GB	200	8	1	40
						BTB01
TIMBAG - FIXINGS INCLUDED						
BP4BP	BP4ZP	BP4GP	100	4	1	10
BP6BP	BP6ZP	BP6GP	150	6	1	10
BP8BP	BP8ZP	BP8GP	200	8	1	10
						BTP01
BRENTON PADBOLT - ELONGATED KEEP						
BAG - EXCLUDES FIXINGS						
-	282004	-	102	4	1	5
						BTB01

Oval Padbolt

Oval padbolts are ideal for securing flush fitting narrow stile gates and doors in domestic and light commercial applications. They are pad-lockable and fixed with carriage bolts for added security.

Technical Data	
Bolt Length (mm)	100
Bolt Ø (mm)	12
Bolt Throw (mm)	40
Plate Size L x W (mm)	55 x 100
Staple Keep Size L x W (mm)	73 x 24
Max. Padlock Shackle Ø (mm)	10
No. of Carriage Bolt Holes	4
Carriage Bolt Ø (mm)	M6

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS						
OP4BB	OP4ZB	OP4GB	100	4	1	60
						BTB03
TIMBAG - FIXINGS INCLUDED						
OP4BP	OP4ZP	OP4GP	100	4	1	10
						BTP03

Heavy Brenton Padbolt

Heavy brenton padbolts are used for securing flush mounted gates and shed doors in heavy domestic, commercial and agricultural applications. They are pad-lockable and fixed with carriage bolts for added security.

Technical Data				
Bolt Length (mm)	150	200	250	300
Bolt Ø (mm)	16	16	16	16
Bolt Throw (mm)	50	50	50	50
Plate Size (mm)	170 x 60	220 x 60	270 x 60	320 x 60
Staple Keep Size L x W (mm)	60 x 40	60 x 40	60 x 40	60 x 40
Max. Padlock Shackle Ø (mm)	14	14	14	14
No. of Carriage Bolt Holes	4	4	4	4
Carriage Bolt Ø (mm)	M6	M6	M6	M6
No. of Screw Holes	6	6	6	6
Screw Ø (mm)	4.0	4.0	4.0	4.0

Product Code	Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS				
282656	150	6	1	40
282219	200	8	1	35
282953	250	10	1	25
282632	300	12	1	20
				BTB01
TIMBAG - FIXINGS INCLUDED				
287258	150	6	1	10
287456	200	8	1	10
287658	250	10	1	10
287477	300	12	1	10
				BTP01

Slide Action Padbolt

Slide action padbolts are ideal for securing flush fitting gates and doors in domestic and light commercial applications when the bolt is exposed externally. They are padlockable and fixed with eight carriage bolts to prevent the bolt being wrenched from the door.

Technical Data	
Bolt Length (mm)	185
Bolt Ø (mm)	9
Bolt Throw (mm)	60
Plate Size L x W (mm)	105 x 72
Staple Keep Size L x W (mm)	76 x 25
Max. Padlock Shackle Ø (mm)	8
No. of Carriage Bolt Holes	8
Carriage Bolt Ø (mm)	M6

Product Code		Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG - EXCLUDES FIXINGS					
282456	282789	185	7 5⁄16	1	80
					BTB04
TIMBAG - FIXINGS INCLUDED					
287114	287585	185	7 5⁄16	1	10
					BTP04

CORROSION RATINGS Epoxy Black Zinc ▶ 1 **2** 3 4 5 Occasionally damp/wet, rural and sheltered areas