

Necked Tower Bolt



Necked tower bolts are used for securing recessed fitting gates and shed doors in a closed position.

Technical Data						
Bolt Length (mm)	100	150	200			
Bolt Ø (mm)	10	10	11			
Bolt Throw (mm)	40	40	50			
Plate Size L x W (mm)	118 x 38	165 x 38	225 x 45			
Flat Keep Size L x W (mm)	43 x 27	43 x 27	43 x 27			
Flat Keep Hole Size (mm)	12	12	12			
No. of Screw Holes	8	10	10			
Screw Ø (mm)	4.0	4.0	4.0			

Product Code		Bolt	Bolt	Pack	Carton
Epoxy Black	Hot Dipped Galvanised	Length (mm)	Length (inch)	Qty (pcs)	Qty (packs)
		BAG - EXCLUDES F	IXINGS		
TBN4BB	TBN4GB	100	4	1	120
TBN6BB	TBN6GB	150	6	1	100
TBN8BB	TBN8GB	200	8	1	40 BTB02
		TIMBAG - FIXINGS IN	ICLUDED		
TBN4BP	TBN4GP	100	4	1	15
TBN6BP	TBN6GP	150	6	1	15
TBN8BP	TBN8GP	200	8	1	15
					RTP02

Straight Tower Bolt



Straight tower bolts are used for securing flush fitting gates and shed doors in a closed position.

Technical Data						
Bolt Length (mm)	75	100	150	200	250	
Bolt Ø (mm)	10	10	10	12	12	
Bolt Throw (mm)	20	25	25	35	35	
Plate Size L x W (mm)	95 x 38	118 x 38	165 x 38	225 x 45	276 x 45	
Staple Keep Size L x W (mm)	39 x 25	39 x 25	46 x 33	46 x 33	46 x 33	
No. of Screw Holes	6	8	10	10	10	
Screw Ø (mm)	4.0	4.0	4.0	4.0	4.0	

	Product Co	de	Bolt	Bolt	Pack	Carton
Epoxy Black	Zinc	Hot Dipped Galvanised	Length (mm)	Length (inch)	Qty (pcs)	Qty (packs)
		BAG - EXC	LUDES FIXIN	IGS		
TBS3BB	TBS3ZB	TBS3GB	75	3	1	100
TBS4BB	TBS4ZB	TBS4GB	100	4	1	120
TBS6BB	TBS6ZB	TBS6GB	150	6	1	100
TBS8BB	TBS8ZB	TBS8GB	200	8	1	40
TBS10BB	TBS10ZB	TBS10GB	250	10	1	40 BTB02
		TIMBAG - FI	XINGS INCLU	JDED		
TBS3BP	TBS3ZP	TBS3GP	75	3	1	15
TBS4BP	TBS4ZP	TBS4GP	100	4	1	15
TBS6BP	TBS6ZP	TBS6GP	150	6	1	15
TBS8BP	TBS8ZP	TBS8GP	200	8	1	15
TBS10BP	TBS10ZP	TBS10GP	250	10	1	15
						BTP02

Heavy Cross Pattern Door Bolt



Heavy cross pattern bolts are typically used for securing large garage $\,$ doors and gates in industrial and agricultural applications. They are extremely strong, pad-lockable and fixed with carriage bolts for high security.

Technical Data					
Bolt Length (mm)	300	450	600		
Bolt Ø (mm)	16	16	16		
Bolt Throw (mm)	70	150	190		
Plate Size L x W (mm)	316 x 64	465 x 64	600 x 64		
Staple Keep Size L x W (mm)	95 x 64	145 x 64	145 x 64		
Staple Plate Size L x W (mm)	65 x 55	65 x 55	65 x 55		
Max. Padlock Shackle Ø (mm)	16	16	16		
No. of Carriage Bolt Holes	6	6	6		
Carriage Bolt Ø (mm)	M8	M8	M8		
No. of Screw Holes	14	14	14		
Screw Ø (mm)	5.0	5.0	5.0		

Product Code	Bolt	Bolt	Pack	Carton	
Hot Dipped Galvanised	Length (mm)	Length (inch)	Qty (pcs)	Qty (packs)	
BAG - EXCLUDES FIXINGS					
282639	300	12	1	2	
282264	450	18	1	2	
282852	600	24	1	2	

Spring Loaded Animal Bolt



Technical Data						
Bolt Length (mm)	143	225	242			
Bolt Ø (mm)	10	12	16			
Bolt Throw (mm)	40	65	65			
Plate Size L x W (mm)	70 x 40	118 x 40	130 x 50			
Staple Plate Size L x W (mm)	50 x 50	50 x 50	65 x 55			
No. of Screw Holes	8	8	8			
Screw Ø (mm)	5.0	5.0	5.0			

Product Code	Bolt	Bolt	Pack	Carton
Hot Dipped Galvanised	Length (mm)	Length (inch)	Qty (pcs)	Qty (packs)
	BAG - EXCL	LUDES FIXINGS		
282454	143	5%	1	20
282565	225	9	1	20
282417	242	9 ½	1	20 BTB06
	TIMBAG - FIX	INGS INCLUDED		
287878	143	5%	1	5
287663	225	9	1	5 BTP05

