

Stitching Screw - For Sheet to Sheet

Bi-Metal (SO)

Exterior (SO)

Zinc



HEX

Used for stitching two metal roofing sheets together without the need to pre-drill a hole (Max. 1.6mm). Self-drilling point and tapered shank, with a washered hexagon head.

Product Code	Size (mm)	Socket Size (mm)	Fixed Washer Ø (mm)	EPDM Washer Thickness (mm)	Max. Drill Thickness (mm)	Effective Thread Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
Bi-Metal (Silver Organic)									
BOX									
BMS22W16	6.3x22	8.0	11.0	16.0	1.6	9	100	35	840
BMR01									
Exterior (Silver Organic)									
BOX									
S22W16B	6.3x22	8.0	12.0	16.0	1.6	9	100	35	840
S25W16B	6.3x25	8.0	12.0	16.0	1.6	12	100	35	840
RF01									
TIMBAG									
S25W16BB	6.3x25	8.0	12.0	16.0	1.6	12	120	5	600
BAG11									
Zinc									
BAG									
ZS22W16	6.3x22	8.0	11.0	16.0	1.6	9	100	22	792
RF02									

Self-Drilling Screw - For Heavy Section Steel

Bi-Metal (SO)

Exterior (SO)

Zinc



HEX

Used for attaching metal to heavy gauge steel (max 12mm) without the need to pre-drill a hole.

Product Code	Size (mm)	Socket Size (mm)	Fixed Washer Ø (mm)	EPDM Washer Thickness (mm)	Max. Drill Thickness (mm)	Effective Thread Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
Bi-Metal (Silver Organic)									
BOX									
BMH38	5.5x38	8.0	11.0	-	12.0	17	100	35	840
BMH38W16	5.5x38	8.0	11.0	16.0	12.0	14	100	15	540
BMH55	5.5x55	8.0	11.0	-	12.0	34	100	15	540
BMR01									
Exterior (Silver Organic)									
BOX									
H32B	5.5x32	8.0	12.0	-	12.0	13	100	35	840
H32W16B	5.5x32	8.0	12.0	16.0	12.0	10	100	15	540
H38B	5.5x38	8.0	12.0	-	12.0	19	100	35	840
H38W16B	5.5x38	8.0	12.0	16.0	12.0	16	100	15	540
H55B	5.5x55	8.0	12.0	-	12.0	36	100	15	540
H55W16B	5.5x55	8.0	12.0	16.0	12.0	33	100	16	384
H65B	5.5x65	8.0	12.0	-	12.0	46	100	15	540
H65W16B	5.5x65	8.0	12.0	16.0	12.0	43	100	16	384
H80B	5.5x80	8.0	12.0	-	12.0	56 *P/T	100	16	384
H80W16B	5.5x80	8.0	12.0	16.0	12.0	53 *P/T	100	16	288
H100B	5.5x100	8.0	12.0	-	12.0	56 *P/T	100	16	288
H100W16B	5.5x100	8.0	12.0	16.0	12.0	53 *P/T	100	12	288
RF01									
BAG									
H38W16BB	5.5x38	8.0	12.0	16.0	12.0	16	100	5	600
BAG11									
Zinc									
BOX									
ZH32B	5.5x32	8.0	12.0	-	12.0	13	100	16	768
ZH32W16B	5.5x32	8.0	12.0	16.0	12.0	10	100	15	540
ZH38B	5.5x38	8.0	12.0	-	12.0	19	100	16	768
ZH38W16B	5.5x38	8.0	12.0	16.0	12.0	16	100	15	540
ZH55B	5.5x55	8.0	12.0	-	12.0	36	100	15	540
ZH55W16B	5.5x55	8.0	12.0	16.0	12.0	33	100	16	384
ZH65B	5.5x65	8.0	12.0	-	12.0	46	100	15	540
ZH65W16B	5.5x65	8.0	12.0	16.0	12.0	43	100	16	384
ZH80B	5.5x80	8.0	12.0	-	12.0	56 *P/T	100	16	384
ZH80W16B	5.5x80	8.0	12.0	16.0	12.0	53 *P/T	100	12	288
ZH100B	5.5x100	8.0	12.0	-	12.0	56 *P/T	100	12	288
ZH100W16B	5.5x100	8.0	12.0	16.0	12.0	53 *P/T	100	12	288
RF02									
BAG									
ZH32W16	5.5x32	8.0	11.0	16.0	12.0	10	100	26	936
ZH38W16	5.5x38	8.0	11.0	16.0	12.0	16	100	24	864
ZH55W16	5.5x55	8.0	11.0	16.0	12.0	33	100	18	648
ZH80W16	5.5x80	8.0	11.0	16.0	12.0	*53 P/T	100	12	432

*P/T = PARTIALLY THREADED

RF02

CORROSION RATINGS

Zinc	▶	1	2	3	4	5	Clean, dry & low humidity environments
Exterior	▶	1	2	3	4	5	Urban & industrial areas with a low salt atmosphere
Bi-Metal (SO)	▶	1	2	3	4	5	Urban & industrial areas with a moderate salt atmosphere