

Reinforced Frames



135 & 141 Range

Zinc

Mart SS



PHILLIPS FRICTION STAY

- Shallow pan head
- Self-tapping thread
- Self-drilling point

For attaching friction stays with countersunk

holes to steel reinforced PVCu frames. *Repair screws for stripped holes (141 range).

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
135Z	3.9 x 16	PH2	1,000	15	540
136Z	3.9 x 19	PH2	1,000	15	540
137Z	3.9 x 25	PH2	1,000	6	288
138Z	3.9 x 29	PH2	1,000	6	288
141Z*	4.8 x 16	PH2	1,000	15	540
142Z*	4.8 x 19	PH2	1,000	8	384
143Z*	4.8 x 23	PH2	1,000	8	384

410 Martensitic SS + Silver Organic					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
135SS	3.9 x 16	PH2	1,000	15	540
136SS	3.9 x 19	PH2	1,000	15	540
137SS	3.9 x 25	PH2	1,000	6	288
138SS	3.9 x 29	PH2	1,000	6	288
143SS*	4.8 x 23	PH2	1,000	9	216

150 Range

Zinc

Yellow



PHILLIPS

- Countersunk head
- Metric thread
- Self-drilling point

An alternative to the self-tapping thread version. This metric

threaded screw has multiple uses for fitting a variety of hardware to frames where there is a steel reinforcement present.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
150Z	M4 x 16	PH2	1,000	15	540
151Z	M4 x 19	PH2	1,000	15	540
153Z	M4 x 25	PH2	1,000	8	384
154Z	M4 x 32	PH2	1,000	8	384
155Z	M4 x 38	PH2	500	8	384

Yellow					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
150Y	M4 x 16	PH2	1,000	15	540
151Y	M4 x 19	PH2	1,000	15	540
153Y	M4 x 25	PH2	1,000	8	384
155Y	M4 x 38	PH2	500	8	384

120 Range

Zinc

Yellow

Mart SS



PHILLIPS

- Countersunk head (*with ribs)
- Self-tapping thread
- Self-drilling point

Multiple uses for fitting a variety of hardware to frames where there is a steel or aluminium reinforcement present.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
120Z*	3.9 x 13	PH2	1,000	15	540
121Z*	3.9 x 16	PH2	1,000	15	540
122Z*	3.9 x 19	PH2	1,000	15	540
123Z	3.9 x 25	PH2	1,000	8	384
126Z	3.9 x 29	PH2	1,000	8	384
124Z	3.9 x 32	PH2	1,000	6	288
125Z	3.9 x 38	PH2	1,000	6	288
127Z	3.9 x 45	PH2	500	8	384

Yellow					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
120Y*	3.9 x 13	PH2	1,000	15	540
121Y*	3.9 x 16	PH2	1,000	15	540
122Y*	3.9 x 19	PH2	1,000	15	540
123Y	3.9 x 25	PH2	1,000	8	384
124Y	3.9 x 32	PH2	1,000	6	288
125Y	3.9 x 38	PH2	1,000	6	288
127Y	3.9 x 45	PH2	500	8	384

410 Martensitic SS + Silver Organic					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
121SS*	3.9 x 16	PH2	1,000	15	540
122SS*	3.9 x 19	PH2	1,000	15	540
123SS	3.9 x 25	PH2	1,000	8	384
124SS	3.9 x 32	PH2	1,000	6	288
125SS	3.9 x 38	PH2	1,000	6	288

230 Range

Zinc

Mart SS



PHILLIPS

- Countersunk facet head
- Metric thread
- Self-drilling point

Frequently used with auto feed machines when 'pinning' steel reinforcement inside PVCu frames.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
230Z	M4 x 13	PH2	1,000	15	540
231Z	M4 x 16	PH2	1,000	15	540
232Z	M4 x 19	PH2	1,000	15	540

410 Martensitic SS + Silver Organic					
Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
231SS	M4 x 16	PH2	1,000	15	540

423 Range

Zinc



PHILLIPS

- Countersunk head
- Self-tapping thread
- Self-drilling point

A heavier gauge screw, generally used where extra strength is required such as attaching hinges to a steel reinforced frame.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
423Z	4.8 x 25	PH2	1,000	6	288
424Z	4.8 x 32	PH2	500	8	384
425Z	4.8 x 38	PH2	500	8	384
427Z	4.8 x 45	PH2	500	6	288
429Z	4.8 x 60	PH2	200	8	384

Shims, Packers & Wedges

For full range, sold in various quantities & sizes
See Page 244

