

STELLA-FIX

UNIVERSAL ANCHOR

EASY INSTALLATION, JUST **PUSH & FIX**

A highly effective universal anchor for fixing heavy loads to plasterboard, cavities and solid materials.

TECHNICAL DATA

Substrate	Plasterboard 12.5mm Thickness	Dense board 15mm Thickness	Double board 25mm Thickness
Anchor Type	Red	Red	Black
Anchor Length (mm)	49	49	59
Drill Hole Ø (mm)	10	10	10
Rec. Tensile Load (kN)	0.33	0.41	0.48
Max Rec. Load (kg)	33	41	48

PERFECT FOR
DOUBLE
BOARD

PERFECT FOR
SINGLE
BOARD



WEIGHTS & MATERIALS

33
KG
**DRYWALL /
PLASTERBOARD**
25mm Thickness

41
KG
**DENSE
BOARD**
25mm Thickness

Up To
48
KG
**DOUBLE
BOARD**
15mm Thickness

PERFECT FOR FITTING



TV Brackets



Radiators



Cabinets

Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------------	------------------	----------------------	----------	----------------	--------------------	--------------------

BOX RED FIXING

STRED55	M5 x 55	49	3 - 18	15	25	10	1200
STRED80	M5 x 80	49	3 - 18	40	25	10	800

BLACK FIXING

STBLACK65	M5 x 65	59	18 - 30	12	25	10	1200
STBLACK90	M5 x 90	59	18 - 30	38	25	10	800

MFT = MAX FIXTURE THICKNESS

ANC04

Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------------	------------------	----------------------	----------	----------------	--------------------

PACK RED FIXING

725374	M5 x 55	49	3 - 18	15	4	5
725146	M5 x 80	49	3 - 18	40	4	5

BLACK FIXING

725012	M5 x 65	59	18 - 30	12	4	5
725973	M5 x 90	59	18 - 30	38	4	5

MFT = MAX FIXTURE THICKNESS

PAK45



DRILL



Drill a 10mm hole in the substrate.

PUSH



Push the Stella-Fix plug firmly into the hole.

INSERT



Insert the Stella-Fix screw through the fixing.

FIX



Tighten the screw until the fixing is secure.