

Cavity Fixings



Spring Toggles

Zinc





A cavity fixing that is ideal for overhead installations.

The wings spread the load over a wider area making them more suited for heavier loads.

11 - 26KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness		
	M3	M5	M6
Screw Ø (mm)	11	14	18
Drill Hole Ø (mm)	20	30	30
Min. Cavity Depth (mm)	0.11	0.22	0.26
Rec. Tensile Load (kN)	11	22	26
Max Rec. Load (kg)			



Product Code	Screw Ø x L (mm)	Wall & Fixture Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
TOG350	M3 x 50	30	100	12	240
TOG550	M5 x 50	20	100	12	192
TOG575	M5 x 75	45	100	12	192
TOG5100	M5 x 100	70	100	6	96
TOG675	M6 x 75	45	100	6	96
					ANC02
TIMBAG					
TOG550B	M5 x 50	20	55	5	600
TOG575B	M5 x 75	45	50	5	600
					BAG23
TIMPAC					
TOG550P	M5 x 50	20	4	5	-
TOG575P	M5 x 75	45	4	5	-
					PAK34

Metal Cavity Anchors

Zinc



COMBI





A cavity fixing that is ideal for hanging radiators, brackets, hand rails and shelving units.

When installing multiple anchors a setting tool is recommended.

22 - 37KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness		
	M4	M5	M6
Screw Ø (mm)	8.0	10.0	12.0
Drill Hole Ø (mm)	4.0	5.0	6.0
Fixture Hole Ø (mm)	0.22	0.22	0.37
Max Rec. Load (kg)	22	22	37



Product Code	Screw Ø x L (mm)	Anchor Length (mm)	Grip Board (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX						
40038CA	M4 x 45	38	8 - 16	100	20	640
40045CA	M4 x 50	45	16 - 23	100	20	640
50037CA	M5 x 45	37	6 - 13	100	20	480
50052CA	M5 x 60	52	7 - 16	100	10	320
50065CA	M5 x 70	65	17 - 32	100	10	320
60052CA	M6 x 60	52	7 - 16	100	10	320
60065CA	M6 x 70	65	17 - 32	100	10	280
						ANC01
TIMBAG						
50037CAB	M5 x 45	37	6 - 13	70	5	600
50052CAB	M5 x 60	52	7 - 16	60	5	600
60065CAB	M6 x 70	65	17 - 32	40	5	600
						BAG22
TIMPAC						
50037CAP	M5 x 45	37	6 - 13	4	5	-
50052CAP	M5 x 60	52	7 - 16	3	5	-
						PAK33

Setting Tool



A handy and efficient tool used to set cavity anchors.

Product Code	Pack Qty (pcs)	Carton Qty (packs)
SETOOL	1	30

BOX

SETOOL	1	30
--------	---	----

Metal Speed Plugs

Zinc



COMBI



A rapid light duty plasterboard fixing for use in a wide range of


applications. Cross-recess head allows simple installation with a screw driver.

Note: Only metal speed plugs come with screws

5 - 14KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness	
	Metal	Nylon
Type	6.0	
Max. Fixture Thickness (mm)	0.14	
Rec. Tensile Load (kN)	14	5
Max Rec. Load (kg)		



Product Code	Plug Length (mm)	Screw Ø x L (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	------------------	------------------	----------------	--------------------	--------------------

BOX					
TBAZS	31.5	4.5 x 30	100	20	640
					ANP01

TUB					
TBAZST	31.5	4.5 x 30	300	20	-
					ANP01

TIMBAG					
TBAZSB	31.5	4.5 x 30	75	5	870
					BAG24

TIMPAC					
TBAZSP	31.5	4.5 x 30	5	5	-
					PAK35

Nylon Speed Plugs



Nylon speed plugs are ideal for electrical installation due to non-conductivity of nylon material.

Note: A 6mm pre-drilled hole may be required in harder plasterboards.

Product Code	Plug Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	------------------	----------------	--------------------	--------------------

BOX				
TBAN	42	100	10	30,000
				ANP02