


Masonry & Concrete Screws

Pan Head



Rapid & Effective
Masonry & Concrete Screws



Ideal for fitting

- Hand rails
- Shelf brackets
- Security lighting
- Metal straps banding

Countersunk



Non-expansion for close to edge fixing



Serrated V-threads for optimum insertion



High-low start threads for rapid pick up

Masonry Screw - Countersunk

Zinc



TX DRIVE



CONCRETE BRICK




BLOCK WOOD



ALL STEEL
NON-FLAMMABLE
FIXING

- Light duty fixing ideal for ironmongery handrails & brackets
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100-150KG

Technical Data

| Substrate | Concrete $\geq 25\text{N/mm}^2$ | | |
|-------------------------------|---------------------------------|-------------------------------|---------------------------|
| | Length (mm) | Drill Hole \varnothing (mm) | Min. Embedment Depth (mm) |
| Length (mm) | 40-80 | 5.0 | 100 |
| Drill Hole \varnothing (mm) | 5.0 | 5.0 | 5.0 |
| Min. Embedment Depth (mm) | 25 | 37 | 37 |
| Min. Drill Hole Depth (mm) | 35 | 47 | 47 |
| Rec. Tensile Load (kN) | 1.00 | 1.50 | 1.50 |
| Max Rec. Load (kg) | 100 | 150 | 150 |

| Product Code | Size (mm) | Driver Bit Size | Max. Fixture Thickness (mm) | Fixture Clearance Hole \varnothing (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------------|-----------|-----------------|-----------------------------|---|----------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) | | | | | | | |
| 640MFCSK | 6.0 x 40 | TX25 | 15 | 6.5 | 100 | 18 | 648 |
| 660MFCSK | 6.0 x 60 | TX25 | 35 | 6.5 | 100 | 12 | 432 |
| 680MFCSK | 6.0 x 80 | TX25 | 55 | 6.5 | 100 | 12 | 432 |
| 6100MFCSK | 6.0 x 100 | TX25 | 63 | 6.5 | 100 | 10 | 360 |

CON14

TIMPAC

| | | | | | | | |
|--------|-----------|------|----|-----|----|----|---|
| 725157 | 6.0 x 40 | TX25 | 15 | 6.5 | 12 | 10 | - |
| 725375 | 6.0 x 60 | TX25 | 35 | 6.5 | 10 | 10 | - |
| 725010 | 6.0 x 80 | TX25 | 55 | 6.5 | 8 | 10 | - |
| 725863 | 6.0 x 100 | TX25 | 63 | 6.5 | 6 | 10 | - |

PAK43

Masonry Screw - Pan Head

Zinc



TX DRIVE



CONCRETE BRICK



BLOCK WOOD



ALL STEEL
NON-FLAMMABLE
FIXING

- Light duty fixing ideal for ironmongery
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100-150KG

Technical Data

| Substrate | Concrete $\geq 25\text{N/mm}^2$ | | |
|-------------------------------|---------------------------------|-------------------------------|---------------------------|
| | Length (mm) | Drill Hole \varnothing (mm) | Min. Embedment Depth (mm) |
| Length (mm) | 40-80 | 5.0 | 100 |
| Drill Hole \varnothing (mm) | 5.0 | 5.0 | 5.0 |
| Min. Embedment Depth (mm) | 25 | 37 | 37 |
| Min. Drill Hole Depth (mm) | 35 | 47 | 47 |
| Rec. Tensile Load (kN) | 1.00 | 1.50 | 1.50 |
| Max Rec. Load (kg) | 100 | 150 | 150 |

| Product Code | Size (mm) | Driver Bit Size | Max. Fixture Thickness (mm) | Fixture Clearance Hole \varnothing (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------------|-----------|-----------------|-----------------------------|---|----------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) | | | | | | | |
| 640MFAN | 6.0 x 40 | TX25 | 15 | 6.5 | 100 | 18 | 648 |
| 660MFAN | 6.0 x 60 | TX25 | 35 | 6.5 | 100 | 12 | 432 |
| 680MFAN | 6.0 x 80 | TX25 | 55 | 6.5 | 100 | 12 | 576 |
| 6100MFAN | 6.0 x 100 | TX25 | 63 | 6.5 | 100 | 10 | 360 |

CON05

TIMPAC

| | | | | | | | |
|--------|----------|------|----|-----|----|----|---|
| 725500 | 6.0 x 40 | TX25 | 15 | 6.5 | 12 | 10 | - |
| 725997 | 6.0 x 60 | TX25 | 35 | 6.5 | 10 | 10 | - |

PAK44