

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Name:** Stain Concealing Paint  
**Product Code:** 237001  
**UFI:** RKC5-4PQF-200T-FNTP  
**Container Size:** 400ml

**REACH registration notes** All chemicals used in this product have been registered under REACH where required.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Spray Paint

### 1.3. Details of the supplier of the safety data sheet

Supplier:	T.I Midwood & Co. Ltd TIMCO House Green Lane Wardle Nantwich CW5 6BJ	T.I Midwood & Co. Ltd Aviemore House Hill Street Monahan Ireland
-----------	---	--

Emergency Help Line: 01865 407333 (24 hour service)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Not Classified

### 2.2. Label elements

#### Hazard pictograms



**Signal word** Danger

**Hazard statements**  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/ container in accordance with national regulations.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P102 Keep out of reach of children.

**Supplemental label information**

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Contains** ACETONE, N-BUTYL ACETATE

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>ACETONE</b>			<b>30-60%</b>
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX	
<b>Classification</b>			
Flam. Liq. 2 - H225			
Eye Irrit. 2 - H319			
STOT SE 3 - H336			
<b>N-BUTYL ACETATE</b>			<b>10-30%</b>
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX	
<b>Classification</b>			
Flam. Liq. 3 - H226			
STOT SE 3 - H336			
<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>			<b>10-30%</b>
<b>&lt;0.1% 1,3 BUTADIENE</b>			
CAS number: 68476-85-7	EC number: 270-704-2		
<b>Classification</b>			
Flam. Gas 1A - H220			
Press. Gas (Liq.) - H280			

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

<b>NAPHTHA (PETROLEUM), HYDRODESULPHURISED HEAVY</b>	<b>&lt;1%</b>	
CAS number: 64742-82-1	EC number: 919-446-0	REACH registration number: 01-2119458049-33-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

The full text for all hazard statements is displayed in Section 16.

**Composition comments** Liquefied petroleum gases (CAS: 68476-85-7) contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation** Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

**Ingestion** Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.

**Skin contact** Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

**Eye contact** Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention promptly if symptoms occur after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause drowsiness and dizziness.

**Ingestion** May cause stomach pain or vomiting.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** Irritating to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Show this safety data sheet to the doctor in attendance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Water spray, foam, dry powder or carbon dioxide.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

**Specific hazards** Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Do not expose to temperatures exceeding 50°C/122°F. Extremely flammable.

**Hazardous combustion products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon.

## 5.3. Advice for firefighters

**Protective actions during firefighting** Use water spray to reduce vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. No smoking, sparks, flames or other sources of ignition near spillage. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours and contact with skin and eyes.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. Provide adequate ventilation. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep in a cool, well ventilated place.

**Storage class** Extremely Flammable Aerosol

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

## ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

## N-BUTYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

## NAPHTHA (PETROLEUM), HYDRODESULPHURISED HEAVY

Long-term exposure limit (8-hour TWA): OES 600 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

### ACETONE (CAS: 67-64-1)

#### DNEL

Workers - Dermal; Long term : 186 mg/kg/day  
Workers - Inhalation; Short term : 2420 mg/m<sup>3</sup>  
Workers - Inhalation; Long term : 1210 mg/m<sup>3</sup>  
Consumer - Oral; Long term : 62 mg/kg/day  
Consumer - Dermal; Long term : 62 mg/kg/day  
Consumer - Inhalation; Long term : 200 mg/m<sup>3</sup>

#### PNEC

Fresh water; 10.6 mg/l  
marine water; 1.06 mg/l  
Intermittent release; 21 mg/l  
Sediment (Freshwater); 30.4 mg/kg/day  
Sediment (Marinewater); 3.04 mg/kg/day  
Soil; 33.3 mg/kg/day  
STP; 100 mg/l

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

### Personal protection

Wear protective clothing.

### Eye/face protection

Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166. Provide eyewash station.

### Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. It is recommended that gloves are made of the following material: Laminate >480 minutes. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The breakthrough time for any glove material may be different for different glove manufacturers.

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

<b>Hygiene measures</b>	Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Observe any occupational exposure limits for the product or ingredients. If ventilation is inadequate, suitable respiratory protection must be worn. Gas filter, type AX. Check that the respirator fits tightly and the filter is changed regularly. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.
<b>Thermal hazards</b>	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<b>Environmental exposure controls</b>	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	White.
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Insoluble in water.
<b>Initial boiling point and range</b>	Liquid base: 126°C
<b>Flash point</b>	A flash point method is not available but the major hazardous component, the liquefied petroleum gases, has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	No information required.
<b>Vapour pressure</b>	3-5 bar @ 25°C
<b>Vapour density</b>	No information required.
<b>Relative density</b>	Liquid base: 1.31-1.35
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	No information available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Liquid base: Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	In use may form flammable/explosive vapour-air mixture.

### 9.2. Other information

<b>Particle size</b>	No information required.
<b>Volatile organic compound</b>	627 g/l

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Stability** Highly volatile.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** No known hazardous reactions if stored under normal conditions.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** Acids. Oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**Summary** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

**Summary** Based on available data the classification criteria are not met.

#### Acute toxicity - inhalation

**Summary** Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

**Summary** Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/irritation

**Summary** Causes serious eye irritation.

#### Respiratory sensitisation

**Summary** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Summary** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Summary** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Summary** Based on available data the classification criteria are not met.

#### Reproductive toxicity

**Summary** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

**Summary** May cause drowsiness or dizziness. Narcotic effect.

## Specific target organ toxicity - repeated exposure

**Summary** Based on available data the classification criteria are not met.

## Aspiration hazard

**Summary** Based on available data the classification criteria are not met.

## Toxicological information on ingredients.

### ACETONE

**Toxicological effects** The toxicity of this substance has been assessed during REACH registration.

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,800.0

**Species** Rat

**ATE oral (mg/kg)** 5,800.0

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 15,800.0

**Species** Rat

**ATE dermal (mg/kg)** 15,800.0

#### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 76.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 76.0

#### Skin sensitisation

**Skin sensitisation** Epidemiological studies have shown no evidence of skin sensitisation.

**Skin contact** Irritating to skin.

**Eye contact** Irritating to eyes.

### N-BUTYL ACETATE

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 14,130.0

**Species** Rat

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 17,600.0

**Species** Rabbit



# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

## Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 29.2

Species Rat

ATE inhalation (vapours mg/l) 29.2

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Toxicological effects** Information given is based on data of the components and of similar products.

### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Not applicable.

### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Not applicable.

### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** LC<sub>50</sub> >20 mg/l, Inhalation, Rat

### Skin corrosion/irritation

**Skin corrosion/irritation** Not irritating.

### Serious eye damage/irritation

**Serious eye damage/irritation** Not irritating.

### Respiratory sensitisation

**Respiratory sensitisation** Not sensitising.

### Skin sensitisation

**Skin sensitisation** Not sensitising.

### Germ cell mutagenicity

**Genotoxicity - in vitro** This substance has no evidence of mutagenic properties.

### Carcinogenicity

**Carcinogenicity** Carcinogenicity in humans is not expected.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Does not contain any substances known to be toxic to reproduction.

### Specific target organ toxicity - single exposure

**STOT - single exposure** A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

<b>Aspiration hazard</b>	Not anticipated to present an aspiration hazard, based on chemical structure.
<b>Inhalation</b>	May cause respiratory system irritation.
<b>Skin contact</b>	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<b>Route of exposure</b>	Inhalation Skin and/or eye contact

## SECTION 12: Ecological information

**Ecotoxicity** The product is not expected to be toxic to aquatic organisms. Avoid the spillage or runoff entering drains, sewers or watercourses.

### Ecological information on ingredients.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Ecotoxicity** Information given is based on data of the components and of similar products.

### 12.1. Toxicity

**Toxicity** Not regarded as dangerous for the environment

### Ecological information on ingredients.

#### ACETONE

##### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** NOEC, 8 hours: 530 mg/l/8 d, Algae

**Acute toxicity - microorganisms** EC<sub>12</sub>, 30 min: 1000 mg/l, Activated sludge

**Acute toxicity - terrestrial** LD<sub>50</sub>, 48 hours: 0.1 - 1 mg/cm<sup>2</sup>, Eisenia Fetida (Earthworm)

##### Chronic aquatic toxicity

**Chronic toxicity - aquatic invertebrates** NOEC, 28 days: 2212 mg/l, Daphnia magna

#### N-BUTYL ACETATE

##### Acute aquatic toxicity

**Acute toxicity - fish**, 96 hours: 100 mg/l, Lepomis macrochirus (Bluegill)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 72 - 205 mg/l, Daphnia magna

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Toxicity** Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

### 12.2. Persistence and degradability

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

**Persistence and degradability** No data available.

## Ecological information on ingredients.

### ACETONE

**Persistence and degradability** The product is readily biodegradable.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Persistence and degradability** The product is readily biodegradable.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

## Ecological information on ingredients.

### ACETONE

**Bioaccumulative potential** BCF: 3, Estimated value.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Bioaccumulative potential** Bioaccumulation is unlikely.

## 12.4. Mobility in soil

**Mobility** No data available.

## Ecological information on ingredients.

### ACETONE

**Mobility** Mobile.

**Adsorption/desorption coefficient** Soil - Kd: 1.5 L/kg @ 20°C

**Henry's law constant** 2.929 - 2.070 Pa m<sup>3</sup>/mol @ 25°C water  
3.311 Pa m<sup>3</sup>/mol @ 25°C marine water

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

## 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## Ecological information on ingredients.

### ACETONE

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**General information** Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Ensure containers are empty before discarding (explosion risk).

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

## **SECTION 14: Transport information**

**General** This product is packed in accordance with the Limited quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS

**Proper shipping name (IMDG)** AEROSOLS

**Proper shipping name (ICAO)** AEROSOLS

**Proper shipping name (ADN)** AEROSOLS

### 14.3. Transport hazard class(es)

**ADR/RID class** 2.1

**ADR/RID classification code** 5F

**ADR/RID label** 2.1

**IMDG class** 2.1

**ICAO class/division** 2.1

**ICAO subsidiary risk** 2.1

# Stain Concealing Paint - Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

ADN class 2.1

## Transport labels



## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

## 14.6. Special precautions for user

IMDG Code segregation group SG69, SW1, SW22

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).  
Control of Substances Hazardous to Health Regulations 2002 (as amended).  
Health and Safety at Work etc. Act 1974 (as amended).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

**Authorisations (Annex XIV Regulation 1907/2006)** No specific authorisations are known for this product.

**Restrictions (Annex XVII Regulation 1907/2006)** No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

# Stain Concealing Paint - Safety Data Sheet

---

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830

**Classification procedures according to Regulation (EC) 1272/2008**      Aerosol 1 - H222, H229: Weight of evidence. Eye Irrit. 2 - H319: Calculation method. STOT SE 3 - H336: Calculation method.

**Hazard statements in full**

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: may burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.