

C2 Strong-Fix Premium Screw

Yellow



POZI



EN 14592:2008

CORROSION RATING


Occasionally damp/wet,
rural and sheltered areas

HARD & SOFT
WOODS

MAN MADE
BOARDS


THIN METAL



PLASTIC

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX						
35012C2	3.5 x 12	6 x 1/2	PZ2	200	140	5040
35016C2	3.5 x 16	6 x 5/8	PZ2	200	140	5040
35020C2	3.5 x 20	6 x 3/4	PZ2	200	75	2700
35025C2	3.5 x 25	6 x 1	PZ2	200	75	2700
35030C2	3.5 x 30	6 x 1 1/4	PZ2	200	75	1800
35040C2	3.5 x 40	6 x 1 1/2	PZ2	200	50	1200
35050C2	3.5 x 50	6 x 2	PZ2	200	35	840
40025C2	4.0 x 25	8 x 1	PZ2	200	75	1800
40030C2	4.0 x 30	8 x 1 1/4	PZ2	200	75	1800
40035C2	4.0 x 35	8 x 1 3/8	PZ2	200	50	1200
40040C2	4.0 x 40	8 x 1 1/2	PZ2	200	50	1200
40045C2	4.0 x 45	8 x 1 3/4	PZ2	200	35	840
40050C2	4.0 x 50	8 x 2	PZ2	200	35	840
40060C2	4.0 x 60	8 x 2 1/2	PZ2	200	15	540
40070C2	4.0 x 70	8 x 2 3/4	PZ2	200	15	540
40080C2	4.0 x 80	8 x 3	PZ2	200	16	384
45030C2	4.5 x 30	9 x 1 1/4	PZ2	200	50	1200
45040C2	4.5 x 40	9 x 1 1/2	PZ2	200	35	840
45050C2	4.5 x 50	9 x 2	PZ2	200	15	540
45060C2	4.5 x 60	9 x 2 1/2	PZ2	200	15	540
45070C2	4.5 x 70	9 x 2 3/4	PZ2	200	16	384
45080C2	4.5 x 80	9 x 3	PZ2	200	16	384
50030C2	5.0 x 30	10 x 1 1/4	PZ2	200	50	1200
50040C2	5.0 x 40	10 x 1 1/2	PZ2	200	35	840
50045C2	5.0 x 45	10 x 1 3/4	PZ2	200	15	540
50050C2	5.0 x 50	10 x 2	PZ2	200	15	540
50060C2	5.0 x 60	10 x 2 1/2	PZ2	200	16	384
50070C2	5.0 x 70	10 x 2 3/4	PZ2	200	16	384
50075C2	5.0 x 75	10 x 2 1/2	PZ2	200	16	384
50080C2	5.0 x 80	10 x 3	PZ2	200	16	384
50090C2	5.0 x 90	10 x 3 1/2	PZ2	100	15	540
50100C2	5.0 x 100	10 x 4	PZ2	100	15	540
50120C2	5.0 x 120	10 x 4 3/4	PZ2	100	15	540
60050C2	6.0 x 50	12 x 2	PZ3	200	16	384
60060C2	6.0 x 60	12 x 2 1/2	PZ3	200	16	384
60070C2	6.0 x 70	12 x 2 3/4	PZ3	200	12	288
60080C2	6.0 x 80	12 x 3	PZ3	200	12	288
60090C2	6.0 x 90	12 x 3 1/2	PZ3	100	15	540
60100C2	6.0 x 100	12 x 4	PZ3	100	15	540
60120C2	6.0 x 120	12 x 4 3/4	PZ3	100	16	384
60130C2	6.0 x 130	12 x 5 1/4	PZ3	100	12	288
60150C2	6.0 x 150	12 x 6	PZ3	100	12	288
60180C2	6.0 x 180	12 x 7 1/4	PZ3	100	8	192
60200C2	6.0 x 200	12 x 8	PZ3	100	8	192

TYPE - CC2

SUB TYPE - CC201

NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above.

Best Seller: C2 Strong-Fix Tubs

C2 Impact Power Bit Included

Designed to handle the most demanding impact driving applications with optimum durability and unbeatable break resistance. Made for Impact Drivers. 10x Longer Life.



Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TUB (C2 IMPACT POWER BIT INCLUDED)						
35025C2TUB	3.5 x 25	6 x 1	PZ2	2,000	4	180
35030C2TUB	3.5 x 30	6 x 1 1/4	PZ2	1,800	4	180
40025C2TUB	4.0 x 25	8 x 1	PZ2	1,700	4	180
40030C2TUB	4.0 x 30	8 x 1 1/4	PZ2	1,500	4	180
40040C2TUB	4.0 x 40	8 x 1 1/2	PZ2	1,200	4	180
40050C2TUB	4.0 x 50	8 x 2	PZ2	800	4	180
40060C2TUB	4.0 x 60	8 x 2 1/2	PZ2	600	4	180
40070C2TUB	4.0 x 70	8 x 2 3/4	PZ2	500	4	180
40080C2TUB	4.0 x 80	8 x 3	PZ2	400	4	180
50040C2TUB	5.0 x 40	10 x 1 1/2	PZ2	800	4	180
50050C2TUB	5.0 x 50	10 x 2	PZ2	600	4	180
50060C2TUB	5.0 x 60	10 x 2 1/2	PZ2	400	4	180
50070C2TUB	5.0 x 70	10 x 2 3/4	PZ2	375	4	180
50080C2TUB	5.0 x 80	10 x 3	PZ2	350	4	180
50090C2TUB	5.0 x 90	10 x 3 1/2	PZ2	325	4	180
50100C2TUB	5.0 x 100	10 x 4	PZ2	300	4	180
60100C2TUB	6.0 x 100	12 x 4	PZ3	225	4	180

TYPE - CCT

SUB TYPE - CCT01

NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above. Qty Break at 20+ tubs

Trade Case

The C2 trade case contains 9 of the most popular sizes in a robust portable case.



Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Screw Qty (pcs)	Tray Qty (pcs)	Carton Qty (packs)
MIXED TRADE CASE						
C25C	-	-	-	-	1,800	10
	3.5 x 16	6 x 5/8	PZ2	480		
	3.5 x 25	6 x 1	PZ2	350		
	4.0 x 30	8 x 1 1/4	PZ2	250		
	4.0 x 40	8 x 1 1/2	PZ2	350		
	4.0 x 50	8 x 2	PZ2	100		
	5.0 x 60	10 x 2 1/2	PZ2	65		
	5.0 x 70	10 x 2 3/4	PZ2	55		
	5.0 x 80	10 x 3	PZ2	100		
	5.0 x 100	10 x 4	PZ2	45		
	Impact Driver Bits		PZ2	5		

TYPE - CC2

SUB TYPE - CC201

NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above.