

## Velocity Premium Multi-Use Screw - Pozi

Yellow



POZI



EN 14592:2008

CORROSION RATING



Occasionally damp/wet, rural and sheltered areas



HARD & SOFT WOODS



MAN MADE BOARDS



THIN METAL



PLASTIC

Product Code	Size (mm)	Thread Length (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	--------------------	-----------------	----------------	--------------------	--------------------

**BOX**

30016VY	3.0 x 16	16	PZ1	200	140	5040
30020VY	3.0 x 20	20	PZ1	200	140	5040
30030VY	3.0 x 30	30	PZ1	200	75	2700
30040VY	3.0 x 40	40	PZ1	200	50	1200
35012VY	3.5 x 12	12	PZ2	200	140	5040
35016VY	3.5 x 16	16	PZ2	200	140	5040
35020VY	3.5 x 20	20	PZ2	200	75	2700
35025VY	3.5 x 25	25	PZ2	200	75	2700
35030VY	3.5 x 30	30	PZ2	200	75	1800
35035VY	3.5 x 35	35	PZ2	200	50	1200
35040VY	3.5 x 40	30	PZ2	200	50	1200
35045VY	3.5 x 45	30	PZ2	200	35	840
35050VY	3.5 x 50	30	PZ2	200	35	840
40016VY	4.0 x 16	16	PZ2	200	75	2700
40020VY	4.0 x 20	20	PZ2	200	75	2700
40025VY	4.0 x 25	25	PZ2	200	75	1800
40030VY	4.0 x 30	30	PZ2	200	75	1800
40035VY	4.0 x 35	35	PZ2	200	50	1200
40040VY	4.0 x 40	30	PZ2	200	50	1200
40045VY	4.0 x 45	30	PZ2	200	35	840
40050VY	4.0 x 50	30	PZ2	200	35	840
40060VY	4.0 x 60	40	PZ2	200	15	540
40070VY	4.0 x 70	40	PZ2	200	15	540
40080VY	4.0 x 80	50	PZ2	200	16	384
45030VY	4.5 x 30	30	PZ2	200	50	1200
45040VY	4.5 x 40	30	PZ2	200	35	840
45050VY	4.5 x 50	30	PZ2	200	15	540
45060VY	4.5 x 60	40	PZ2	200	15	540
45070VY	4.5 x 70	40	PZ2	200	16	384
45080VY	4.5 x 80	50	PZ2	200	16	384
50030VY	5.0 x 30	30	PZ2	200	50	1056
50040VY	5.0 x 40	30	PZ2	200	35	840
50045VY	5.0 x 45	30	PZ2	200	15	540
50050VY	5.0 x 50	30	PZ2	200	15	540
50060VY	5.0 x 60	40	PZ2	200	16	384
50070VY	5.0 x 70	40	PZ2	200	16	384
50075VY	5.0 x 75	40	PZ2	200	16	384
50080VY	5.0 x 80	50	PZ2	200	16	384
50090VY	5.0 x 90	60	PZ2	100	15	540
50100VY	5.0 x 100	60	PZ2	100	15	540
60040VY	6.0 x 40	30	PZ3	200	15	540
60045VY	6.0 x 45	30	PZ3	200	15	540
60050VY	6.0 x 50	30	PZ3	200	16	384
60060VY	6.0 x 60	40	PZ3	200	16	384
60070VY	6.0 x 70	40	PZ3	200	12	288
60080VY	6.0 x 80	50	PZ3	200	12	288
60090VY	6.0 x 90	60	PZ3	100	15	540
60100VY	6.0 x 100	70	PZ3	100	15	540
60120VY	6.0 x 120	70	PZ3	100	16	384
60130VY	6.0 x 130	70	PZ3	100	12	384
60150VY	6.0 x 150	70	PZ3	100	12	324
60180VY	6.0 x 180	70	PZ3	100	8	192
60200VY	6.0 x 200	70	PZ3	100	8	192

TYPE - VEL

SUB TYPE - VEL01

NEW: Velocity Tubs



Product Code	Size (mm)	TL (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	---------	-----------------	----------------	--------------------	--------------------

**TUB (DRIVER BIT INCLUDED)**

40030VYTUB	4.0 x 30	30	PZ2	1,500	4	180
40040VYTUB	4.0 x 40	30	PZ2	1,200	4	180
40050VYTUB	4.0 x 50	30	PZ2	800	4	180
50040VYTUB	5.0 x 40	30	PZ2	800	4	180
50050VYTUB	5.0 x 50	30	PZ2	600	4	180
50060VYTUB	5.0 x 60	40	PZ2	400	4	180
50070VYTUB	5.0 x 70	40	PZ2	375	4	180
50080VYTUB	5.0 x 80	50	PZ2	350	4	180
50090VYTUB	5.0 x 90	60	PZ2	325	4	180
50100VYTUB	5.0 x 100	60	PZ2	300	4	180

TYPE - VEL | SUB TYPE - VEL01

TL = THREAD LENGTH

## Velocity Premium Multi-Use Screw - TX Drive

Yellow



TX DRIVE



EN 14592:2008

CORROSION RATING



Occasionally damp/wet, rural and sheltered areas



HARD & SOFT WOODS



MAN MADE BOARDS



THIN METAL



PLASTIC

Product Code	Size (mm)	TL (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	---------	-----------------	----------------	--------------------	--------------------

**BOX**

50050VYTX	5.0 x 50	30	TX25	200	15	540
50060VYTX	5.0 x 60	40	TX25	200	16	384
50070VYTX	5.0 x 70	40	TX25	200	16	384
50080VYTX	5.0 x 80	50	TX25	200	16	384
50100VYTX	5.0 x 100	60	TX25	100	15	540
60080VYTX	6.0 x 80	50	TX30	200	12	288
60100VYTX	6.0 x 100	70	TX30	100	15	540
60120VYTX	6.0 x 120	70	TX30	100	16	384
60150VYTX	6.0 x 150	70	TX30	100	12	324
60180VYTX	6.0 x 180	70	TX30	100	8	192
60200VYTX	6.0 x 200	70	TX30	100	8	192
80200VYTX	8.0 x 200	80	TX40	50	8	192
80225VYTX	8.0 x 225	80	TX40	50	8	192
80250VYTX	8.0 x 250	80	TX40	50	9	216
80275VYTX	8.0 x 275	80	TX40	25	9	216
80300VYTX	8.0 x 300	80	TX40	25	9	216

TYPE - VEL | SUB TYPE - VEL02

TL = THREAD LENGTH