

Coach Screws



Coach Screw

Zinc

HEX EN 14592:2008

CORROSION RATING

1 2 3 4 5

Clean, dry & low humidity environments

A traditional heavy duty woodscrew mainly used for timber to timber applications, attaching ironmongery to timber or for use with a nylon plug into masonry. Pilot holes may be required into certain hard woods.

NOTE: Thread length is 2/3 of the overall length screw.
E.g. 100mm = 60mm thread.

Exterior Coach Screws

Page 35

Product Code	Size (mm)	Socket Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
0625CSC	6.0 x 25	10	250	12	432
0630CSC	6.0 x 30	10	200	12	540
0640CSC	6.0 x 40	10	200	12	432
0650CSC	6.0 x 50	10	200	8	240
0660CSC	6.0 x 60	10	200	8	240
0670CSC	6.0 x 70	10	200	8	240
0675CSC	6.0 x 75	10	100	12	432
0680CSC	6.0 x 80	10	100	12	432
06100CSC	6.0 x 100	10	200	6	180
0830CSC	8.0 x 30	13	200	8	240
0840CSC	8.0 x 40	13	200	8	240
0850CSC	8.0 x 50	13	100	12	432
0860CSC	8.0 x 60	13	100	8	240
0865CSC	8.0 x 65	13	100	8	240
0870CSC	8.0 x 70	13	100	8	240
0875CSC	8.0 x 75	13	100	8	240
0880CSC	8.0 x 80	13	100	8	240
0890CSC	8.0 x 90	13	50	12	432
08100CSC	8.0 x 100	13	50	12	432
08120CSC	8.0 x 120	13	50	12	432
08150CSC	8.0 x 150	13	50	8	240
1040CSC	10.0 x 40	17	100	8	240
1050CSC	10.0 x 50	17	100	8	240
1060CSC	10.0 x 60	17	100	6	180
1070CSC	10.0 x 70	17	100	6	180
1075CSC	10.0 x 75	17	100	6	180
1080CSC	10.0 x 80	17	50	8	240
10100CSC	10.0 x 100	17	50	8	240
10120CSC	10.0 x 120	17	50	8	240
10130CSC	10.0 x 130	17	50	8	240
10150CSC	10.0 x 150	17	25	12	432
10160CSC	10.0 x 160	17	25	12	432
10200CSC	10.0 x 200	17	20	12	432
1250CSC	12.0 x 50	19	100	6	180
1275CSC	12.0 x 75	19	50	8	240
1280CSC	12.0 x 80	19	25	12	432
12100CSC	12.0 x 100	19	25	12	432
12150CSC	12.0 x 150	19	25	8	240

TYPE - COA SUB TYPE - COA01

Product Code	Size (mm)	Socket Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG					
0650CSCB	6.0 x 50	10	120	5	600
0670CSCB	6.0 x 70	10	100	5	600
06100CSCB	6.0 x 100	10	70	5	600
0850CSCB	8.0 x 50	13	75	5	600
0860CSCB	8.0 x 60	13	65	5	600
0880CSCB	8.0 x 80	13	48	5	600
08100CSCB	8.0 x 100	13	40	5	600
1050CSCB	10.0 x 50	17	45	5	600
1080CSCB	10.0 x 80	17	30	5	600
10100CSCB	10.0 x 100	17	28	5	600
10120CSCB	10.0 x 120	17	24	5	600
10130CSCB	10.0 x 130	17	23	5	600
10150CSCB	10.0 x 150	17	18	5	600
1280CSCB	12.0 x 80	19	25	5	600
12100CSCB	12.0 x 100	19	20	5	600
12150CSCB	12.0 x 150	19	12	5	600
TYPE - BAG					SUB TYPE - BAG06
TIMPAC					
0650CSCP	6.0 x 50	10	10	5	-
0670CSCP	6.0 x 70	10	10	5	-
0680CSCP	6.0 x 80	10	10	5	-
06100CSCP	6.0 x 100	10	10	5	-
0850CSCP	8.0 x 50	13	5	5	-
0860CSCP	8.0 x 60	13	5	5	-
0880CSCP	8.0 x 80	13	5	5	-
08100CSCP	8.0 x 100	13	5	5	-
1050CSCP	10.0 x 50	17	4	5	-
1080CSCP	10.0 x 80	17	4	5	-
10100CSCP	10.0 x 100	17	2	5	-
10150CSCP	10.0 x 150	17	2	5	-
1275CSCP	12.0 x 75	19	2	5	-
TYPE - PAK					SUB TYPE - PAK12

Coach Screw With Nylon Plug

Zinc **Nylon**

HEX

A traditional heavy duty woodscrew with a nylon plug for masonry applications.

Product Code	Screw Size (mm)	Plug Size (mm)	Socket Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG						
0660CSCNB	6.0 x 60	10 x 50	10	40	5	600
0680CSCNB	6.0 x 80	10 x 50	10	30	5	600
08100CSCNB	8.0 x 100	12 x 60	13	12	5	600
TYPE - BAG						SUB TYPE - BAG06
TIMPAC						
0660CSCNP	6.0 x 60	10 x 50	10	2	5	-
0680CSCNP	6.0 x 80	10 x 50	10	2	5	-
08100CSCNP	8.0 x 100	12 x 60	13	2	5	-
TYPE - PAK						SUB TYPE - PAK12

Nylon Plug

Nylon

Product Code	Size (mm)	To Fit Screw Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG					
06NLPB	6.0 x 30	3.5 - 5.0	200	5	870
08NLPB	8.0 x 40	5.0 - 6.0	100	5	870
10NLPB	10.0 x 50	6.0 - 8.0	70	5	600
TYPE - BAG					SUB TYPE - BAG07
TIMPAC					
06NLPB	6.0 x 30	3.5 - 5.0	20	10	-
08NLPB	8.0 x 40	5.0 - 6.0	10	10	-
10NLPB	10.0 x 50	6.0 - 8.0	5	10	-
12NLPB	12.0 x 60	8.0 - 10.0	2	10	-
TYPE - PAK					SUB TYPE - PAK13

Nylon plug for use with coach screws into masonry.