

Stitching Screw - For Sheet to Sheet

Bi-Metal (SO)

Exterior (SO)

Zinc



CORROSION RATING



Urban & industrial areas with a moderate salt atmosphere

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

CORROSION RATING



Clean, dry & low humidity environments



HEX

Used for stitching two metal roofing sheets together without the need to pre-drill a hole (Max. 1.6mm). Self-drilling point and tapered shank, with a washered hexagon head.

| Product Code | Size (mm) | Socket Size (mm) | Fixed Washer Ø (mm) | EPDM Washer (mm) | Max. Drill Thickness (mm) | Effective Thread Length (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|--------------|-----------|------------------|---------------------|------------------|---------------------------|------------------------------|----------------|--------------------|--------------------|
|--------------|-----------|------------------|---------------------|------------------|---------------------------|------------------------------|----------------|--------------------|--------------------|

Bi-Metal (Silver Organic)

BOX

| | | | | | | | | | |
|------------|----------|------------------|------|------|-----|---|-----|----|-----|
| BMS22W16 | 6.3 x 22 | 8.0 | 11.0 | 16.0 | 1.6 | 9 | 100 | 35 | 840 |
| TYPE - BMR | | SUB TYPE - BMR01 | | | | | | | |

Exterior (Silver Organic)

BOX

| | | | | | | | | | |
|---------|----------|-----|------|------|-----|----|-----|----|-----|
| S22W16B | 6.3 x 22 | 8.0 | 12.0 | 16.0 | 1.6 | 9 | 100 | 35 | 840 |
| S25W16B | 6.3 x 25 | 8.0 | 12.0 | 16.0 | 1.6 | 12 | 100 | 35 | 840 |

TIMBAG

| | | | | | | | | | |
|-------------------------------|----------|------------------------|------|------|-----|----|-----|---|-----|
| S25W16BB | 6.3 x 25 | 8.0 | 12.0 | 16.0 | 1.6 | 12 | 120 | 5 | 600 |
| TYPE - RF (BOX), BAG (TIMBAG) | | SUB TYPE - RF01, BAG11 | | | | | | | |

Zinc

BAG

| | | | | | | | | | |
|-----------|----------|-----------------|------|------|-----|---|-----|----|-----|
| ZS22W16 | 6.3 x 22 | 8.0 | 11.0 | 16.0 | 1.6 | 9 | 100 | 22 | 792 |
| TYPE - RF | | SUB TYPE - RF02 | | | | | | | |

Self-Drilling Screw - For Heavy Section Steel

Bi-Metal (SO)

Exterior (SO)

Zinc



CORROSION RATING



Urban & industrial areas with a moderate salt atmosphere

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

CORROSION RATING



Clean, dry & low humidity environments



HEX

Used for attaching metal to heavy gauge steel (max 12mm) without the need to pre-drill a hole.

| Product Code | Size (mm) | Socket Size (mm) | Fixed Washer Ø (mm) | EPDM Washer (mm) | Max. Drill T (mm) | Effective Thread Length (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|--------------|-----------|------------------|---------------------|------------------|-------------------|------------------------------|----------------|--------------------|--------------------|
|--------------|-----------|------------------|---------------------|------------------|-------------------|------------------------------|----------------|--------------------|--------------------|

Bi-Metal (Silver Organic)

BOX

| | | | | | | | | | |
|------------|----------|------------------------------|------|------|------|----|-----|----|-----|
| BMH38 | 5.5 x 38 | 8.0 | 11.0 | - | 12.0 | 17 | 100 | 35 | 840 |
| BMH38W16 | 5.5 x 38 | 8.0 | 11.0 | 16.0 | 12.0 | 14 | 100 | 15 | 540 |
| BMH55 | 5.5 x 55 | 8.0 | 11.0 | - | 12.0 | 34 | 100 | 15 | 540 |
| BMH55W16 | 5.5 x 55 | 8.0 | 11.0 | 16.0 | 12.0 | 31 | 100 | 16 | 384 |
| TYPE - BMR | | SUB TYPE - BMR01 T=THICKNESS | | | | | | | |

Exterior (Silver Organic)

BOX

| | | | | | | | | | |
|-----------|-----------|-----------------------------|------|------|------|---------|-----|----|-----|
| H32B | 5.5 x 32 | 8.0 | 12.0 | - | 12.0 | 13 | 100 | 35 | 840 |
| H32W16B | 5.5 x 32 | 8.0 | 12.0 | 16.0 | 12.0 | 10 | 100 | 15 | 540 |
| H38B | 5.5 x 38 | 8.0 | 12.0 | - | 12.0 | 19 | 100 | 35 | 840 |
| H38W16B | 5.5 x 38 | 8.0 | 12.0 | 16.0 | 12.0 | 16 | 100 | 15 | 540 |
| H55B | 5.5 x 55 | 8.0 | 12.0 | - | 12.0 | 36 | 100 | 15 | 540 |
| H55W16B | 5.5 x 55 | 8.0 | 12.0 | 16.0 | 12.0 | 33 | 100 | 16 | 384 |
| H65B | 5.5 x 65 | 8.0 | 12.0 | - | 12.0 | 46 | 100 | 15 | 540 |
| H65W16B | 5.5 x 65 | 8.0 | 12.0 | 16.0 | 12.0 | 43 | 100 | 16 | 384 |
| H80B | 5.5 x 80 | 8.0 | 12.0 | - | 12.0 | 56 *P/T | 100 | 16 | 384 |
| H80W16B | 5.5 x 80 | 8.0 | 12.0 | 16.0 | 12.0 | 53 *P/T | 100 | 16 | 288 |
| H100B | 5.5 x 100 | 8.0 | 12.0 | - | 12.0 | 56 *P/T | 100 | 16 | 288 |
| H100W16B | 5.5 x 100 | 8.0 | 12.0 | 16.0 | 12.0 | 53 *P/T | 100 | 12 | 288 |
| TYPE - RF | | SUB TYPE - RF01 T=THICKNESS | | | | | | | |

BAG

| | | | | | | | | | |
|------------|----------|------------------------------|------|------|------|----|-----|---|-----|
| H38W16BB | 5.5 x 38 | 8.0 | 12.0 | 16.0 | 12.0 | 16 | 100 | 5 | 600 |
| TYPE - BAG | | SUB TYPE - BAG11 T=THICKNESS | | | | | | | |

Zinc

BOX

| | | | | | | | | | |
|-----------|-----------|-----------------------------|------|------|------|---------|-----|----|-----|
| ZH32B | 5.5 x 32 | 8.0 | 12.0 | - | 12.0 | 13 | 100 | 16 | 768 |
| ZH32W16B | 5.5 x 32 | 8.0 | 12.0 | 16.0 | 12.0 | 10 | 100 | 15 | 540 |
| ZH38B | 5.5 x 38 | 8.0 | 12.0 | - | 12.0 | 19 | 100 | 16 | 768 |
| ZH38W16B | 5.5 x 38 | 8.0 | 12.0 | 16.0 | 12.0 | 16 | 100 | 15 | 540 |
| ZH55B | 5.5 x 55 | 8.0 | 12.0 | - | 12.0 | 36 | 100 | 15 | 540 |
| ZH55W16B | 5.5 x 55 | 8.0 | 12.0 | 16.0 | 12.0 | 33 | 100 | 16 | 384 |
| ZH65B | 5.5 x 65 | 8.0 | 12.0 | - | 12.0 | 46 | 100 | 15 | 540 |
| ZH65W16B | 5.5 x 65 | 8.0 | 12.0 | 16.0 | 12.0 | 43 | 100 | 16 | 384 |
| ZH80B | 5.5 x 80 | 8.0 | 12.0 | - | 12.0 | 56 *P/T | 100 | 16 | 384 |
| ZH80W16B | 5.5 x 80 | 8.0 | 12.0 | 16.0 | 12.0 | 53 *P/T | 100 | 12 | 288 |
| ZH100B | 5.5 x 100 | 8.0 | 12.0 | - | 12.0 | 56 *P/T | 100 | 12 | 288 |
| ZH100W16B | 5.5 x 100 | 8.0 | 12.0 | 16.0 | 12.0 | 53 *P/T | 100 | 12 | 288 |
| TYPE - RF | | SUB TYPE - RF02 T=THICKNESS | | | | | | | |

BAG

| | | | | | | | | | |
|-----------|----------|-----------------------------|------|------|------|---------|-----|----|-----|
| ZH32W16 | 5.5 x 32 | 8.0 | 11.0 | 16.0 | 12.0 | 10 | 100 | 26 | 936 |
| ZH38W16 | 5.5 x 38 | 8.0 | 11.0 | 16.0 | 12.0 | 16 | 100 | 24 | 864 |
| ZH55W16 | 5.5 x 55 | 8.0 | 11.0 | 16.0 | 12.0 | 33 | 100 | 18 | 648 |
| ZH80W16 | 5.5 x 80 | 8.0 | 11.0 | 16.0 | 12.0 | *53 P/T | 100 | 12 | 432 |
| TYPE - RF | | SUB TYPE - RF02 T=THICKNESS | | | | | | | |

*P/T = Partially Threaded