

Metal Framing Screws



Low Profile - Pan Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere




STEEL

A light duty metal to metal screw with a reduced pan to give a flush finish. Silver organic plated to withstand over 500 hours salt spray test.

| Product Code | Size (mm) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------------|-----------|------------------------------|------------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) | | | | | |
| LPP16 | 4.8 x 16 | 4.0 | 500 | 15 | 768 |
| TYPE - MFS | | | SUB TYPE - MFS01 | | |

Low Profile - Wafer Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere



STEEL

A light duty metal to metal screw with a large flat surface under the head, making it ideal for fixing thinner sheet material when a flush finish is required. Silver Organic plated to withstand over 500 hours salt spray test.

| Product Code | Size (mm) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------------|-----------|------------------------------|------------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) | | | | | |
| 22LPW | 4.8 x 22 | 4.0 | 200 | 35 | 840 |
| TYPE - MFS | | | SUB TYPE - MFS01 | | |

Low Profile - Pancake Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere



STEEL


A medium duty metal to metal screw with a large flat surface under the head, making it ideal for fixing thinner sheet material when a flush finish is required. Silver organic plated to withstand over 500 hours salt spray test.



| Product Code | Size (mm) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------------|-----------|------------------------------|------------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) | | | | | |
| FP19 | 5.5 x 19 | 5.0 | 500 | 16 | 540 |
| FP26 | 5.5 x 26 | 5.0 | 500 | 16 | 384 |
| TYPE - MFS | | | SUB TYPE - MFS01 | | |

Pan Head

Zinc



Clean, dry & low humidity environments



STEEL

A light duty metal to metal screw with a phillips recess used for interior applications.

| Product Code | Size (imp.) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|--------------|-------------|------------------------------|------------------|--------------------|--------------------|
| BOX | | | | | |
| 00658PPSD | 6 x 3/4 | 2.5 | 1,000 | 15 | 540 |
| 00061PPSD | 6 x 1 | 2.5 | 1,000 | 16 | 384 |
| 07716PPSD | 7 x 7/16 | 2.5 | 1,000 | 15 | 540 |
| 00812PPSD | 8 x 1/2 | 3.0 | 1,000 | 15 | 540 |
| 812PSD | 8 x 1/2 | 3.0 | 200 | 15 | 2700 |
| 00834PPSD | 8 x 3/4 | 3.0 | 1,000 | 16 | 384 |
| 834PSD | 8 x 3/4 | 3.0 | 200 | 75 | 2700 |
| 00081PPSD | 8 x 1 | 3.0 | 1,000 | 12 | 288 |
| 81PSD | 8 x 1 | 3.0 | 200 | 75 | 2700 |
| TYPE - PPS | | | SUB TYPE - PPS01 | | |

Pan Head

Zinc



Clean, dry & low humidity environments



STEEL

A light duty metal to metal screw with a square recess used for interior applications.

| Product Code | Size (imp.) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|--------------|-------------|------------------------------|------------------|--------------------|--------------------|
| BOX | | | | | |
| 00812SPSD | 8 x 1/2 | 3.0 | 1,000 | 15 | 540 |
| TYPE - PPS | | | SUB TYPE - PPS01 | | |

Wafer Head

Zinc



Clean, dry & low humidity environments

SELF-DRILLING POINT
EN 10666:2008



SHARP POINT



STEEL THIN SHEET

Used when constructing drywall track and ceiling track systems to stitch the track together

| Product Code | Size (mm) | Max. Drilling Thickness (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|----------------------------|-----------|------------------------------|------------------|--------------------|--------------------|
| BOX | | | | | |
| Self-drilling point | | | | | |
| 08916WHSD | 4.2 x 13 | 3.0 | 1,000 | 15 | 360 |
| 00016WHSD | 4.2 x 16 | 3.0 | 1,000 | 16 | 288 |
| 00019WHSD | 4.2 x 19 | 3.0 | 1,000 | 12 | 288 |
| 00025WHSD | 4.2 x 25 | 3.0 | 1,000 | 12 | 144 |
| Sharp point | | | | | |
| 08916WHSP | 4.2 x 13 | 0.6 | 1,000 | 15 | 540 |
| TYPE - WHS | | | SUB TYPE - WHS01 | | |