

STELLA-FIX

UNIVERSAL ANCHOR

EASY INSTALLATION, JUST **PUSH & FIX**

A highly effective universal anchor for fixing heavy loads to plasterboard, cavities and solid materials.

TECHNICAL DATA

Substrate	Plasterboard 12.5mm Thickness	Dense board 15mm Thickness	Double board 25mm Thickness
Anchor Type	Red	Red	Black
Anchor Length (mm)	49	49	59
Drill Hole Ø (mm)	10	10	10
Rec. Tensile Load (kN)	0.33	0.41	0.48
Max Rec. Load (kg)	33	41	48

WEIGHTS & MATERIALS

33
KG

**DRYWALL /
PLASTERBOARD**
12.5mm
Thickness

41
KG

**DOUBLE
BOARD**
25mm
Thickness

Up To
48
KG

**DENSE
BOARD**
15mm
Thickness



**PERFECT
FOR
DOUBLE
BOARD**

**PERFECT
FOR
SINGLE
BOARD**

PERFECT FOR FITTING



TV Brackets



Radiators



Cabinets

Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX							
RED FIXING							
STRED55	M5 x 55	49	3 - 18	15	25	20	1200
STRED80	M5 x 80	49	3 - 18	40	25	10	800
BLACK FIXING							
STBLACK65	M5 x 65	59	18 - 30	12	25	20	1200
STBLACK90	M5 x 90	59	18 - 30	38	25	10	800

TYPE - ANC SUB TYPE - ANC04


MFT = Max Fixture Thickness.

Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)
PACK						
RED FIXING						
725374	M5 x 55	49	3 - 18	15	4	5
725146	M5 x 80	49	3 - 18	40	4	5
BLACK FIXING						
725012	M5 x 65	59	18 - 30	12	4	5
725973	M5 x 90	59	18 - 30	38	4	5

TYPE - PAK SUB TYPE - PAK47


MFT = Max Fixture Thickness.

DRILL




Drill a 10mm hole in the substrate.

PUSH



Push the Stella-Fix plug firmly into the hole.

INSERT



Insert the Stella-Fix screw through the fixing.

FIX



Tighten the screw until the fixing is secure.