

Masonry Bolt - Hex Head

Exterior



HEX



Concrete



BRICK



BLOCK



WOOD

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Socket Size (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	------------------	----------	----------------	--------------------	--------------------

BOX

MF650	6.0 x 50*	10	20	100	10	300
MF675	6.0 x 75*	10	45	100	6	180
MF6100	6.0 x 100*	10	55	100	6	180
MF6130	6.0 x 130*	10	85	100	6	180
MF6150	6.0 x 150*	10	105	75	6	180
MF860	8.0 x 60	15	20	100	6	180
MF875	8.0 x 75	15	35	100	6	180
MF8100	8.0 x 100	15	60	50	10	300
MF8130	8.0 x 130	15	90	50	6	180
MF8150	8.0 x 150	15	110	50	6	180
MF1060	10.0 x 60	17	10	50	10	300
MF1075	10.0 x 75	17	25	50	6	180
MF10100	10.0 x 100	17	50	50	6	180
MF10130	10.0 x 130	17	80	50	6	180
MF10150	10.0 x 150	17	100	25	6	180
MF1275	12.0 x 75	19	15	50	9	180
MF12100	12.0 x 100	19	40	25	10	300
MF12130	12.0 x 130	19	70	25	6	180
MF12150	12.0 x 150	19	90	25	6	180
MF12200	12.0 x 200	19	140	25	4	120
MF16100	16.0 x 100	27	20	10	8	240
MF16150	16.0 x 150	27	70	10	6	180

TYPE - SKU

SUB TYPE - SKU01

TIMBAG

MF650B	6.0 x 50*	10	20	64	5	600
MF860B	8.0 x 60	15	20	30	5	600
MF875B	8.0 x 75	15	35	26	5	600
MF8100B	8.0 x 100	15	60	20	5	600
MF1060B	10.0 x 60	17	10	18	5	600
MF1075B	10.0 x 75	17	25	14	5	600
MF10100B	10.0 x 100	17	50	12	5	600
MF10150B	10.0 x 150	17	100	8	5	600
MF1275B	12.0 x 75	19	15	12	5	600
MF12100B	12.0 x 100	19	40	8	5	600
MF12130B	12.0 x 130	19	70	6	5	600
MF12150B	12.0 x 150	19	90	6	5	600

TYPE - BAG

SUB TYPE - BAG32

TIMPAC

MF650PRE	6.0 x 50*	10	20	4	5	-
MF875PRE	8.0 x 75	15	35	4	5	-
MF8100PRE	8.0 x 100	15	60	4	5	-
MF1075PRE	10.0 x 75	17	25	4	5	-
MF10100PRE	10.0 x 100	17	50	2	5	-
MF10130PRE	10.0 x 130	17	80	2	5	-
MF10150PRE	10.0 x 150	17	100	2	5	-
MF12100PRE	12.0 x 100	19	40	2	5	-
MF12150PRE	12.0 x 150	19	90	2	5	-
MF16100PRE	16.0 x 100	27	20	2	5	-
MF16150PRE	16.0 x 150	27	70	2	5	-

TYPE - PAK SUB TYPE - PAK43 MFT = MAX FIXTURE THICKNESS

Masonry Bolt - Countersunk

Exterior



TX DRIVE



Concrete



BRICK



BLOCK



WOOD

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Driver Bit Size	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	-----------------	----------	----------------	--------------------	--------------------

BOX (DRIVER BIT INCLUDED)

MF860C	8.0 x 60	TX40	20	100	6	180
MF875C	8.0 x 75	TX40	35	100	6	180
MF8100C	8.0 x 100	TX40	60	50	8	240
MF1060C	10.0 x 60	TX50	10	50	8	240
MF1075C	10.0 x 75	TX50	25	50	6	180
MF10100C	10.0 x 100	TX50	50	50	6	180

TYPE - SKU SUB TYPE - SKU02

MFT = MAX FIXTURE THICKNESS

Masonry Bolt - Pan Head

Exterior



TX DRIVE



Concrete



BRICK



BLOCK



WOOD

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Driver Bit Size	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	-----------------	----------	----------------	--------------------	--------------------

BOX (DRIVER BIT INCLUDED)

MF860P	8.0 x 60	TX40	20	100	6	180
MF875P	8.0 x 75	TX40	35	100	4	180
MF8100P	8.0 x 100	TX40	60	50	6	300
MF1060P	10.0 x 60	TX50	10	50	6	300
MF1075P	10.0 x 75	TX50	25	50	6	180
MF10100P	10.0 x 100	TX50	50	50	6	180

TYPE - SKU

SUB TYPE - SKU03

MFT = MAX FIXTURE THICKNESS

* Please note: 6.0mm diameter bolts have a hex flange head.