

## Forged Eye & Shield

Yellow



CONCRETE BRICK STONE

CORROSION RATING



Clean, dry & low humidity environments

Complete with three segment shield anchors, a forged eye for extra strength.


Ideal for attaching ropes or cables.

- Yellow passivated for

improved corrosion resistance

- Nut and washer included
- Grade 4.8

Please see previous page for shield installation



Once shield is in place Tighten nut while keeping eye still Tighten to rec. torque

Product Code	Thread Ø x L (mm)	Eye Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-------------------	------------	----------------	--------------------	--------------------

### TIMBAG

06EYEB	M6 x 50	8.0	18	5	870
08EYEB	M8 x 60	10.0	14	5	870

TYPE - BAG SUB TYPE - BAG30

### TIMPAC

06EYEP	M6 x 50	8	2	10	-
08EYEP	M8 x 60	10	2	10	-
10EYEP	M10 x 73	12	2	10	-

TYPE - PAK SUB TYPE - PAK49

## Forged Eye Only

Yellow



CORROSION RATING



Clean, dry & low humidity environments

A useful threaded eye bolt for attaching ropes or cables. Manufactured using a forging process for extra strength.

Sold without shield anchor.

Product Code	Thread Ø x L (mm)	Eye Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-------------------	------------	----------------	--------------------	--------------------

### BOX

06EYEB	M6 x 50	8	50	18	648
08EYEB	M8 x 60	10	50	10	300
10EYEB	M10 x 73	12	50	8	240
12EYEB	M12 x 95	16	25	8	240

TYPE - SHA SUB TYPE - SHA01


## Forged Hook & Shield

Yellow



CONCRETE BRICK STONE

CORROSION RATING



Clean, dry & low humidity environments


Manufactured using a forging process, to prevent opening out the hook when load is applied. Complete with three segment shield anchor.

- Yellow passivated for

improved corrosion resistance

- Nut and washer included
- Grade 4.8

Please see previous page for shield installation



Once shield is in place Tighten nut while keeping hook still Tighten until secure

Product Code	Thread Ø x Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	------------------------	----------------	--------------------	--------------------

### TIMBAG

06HOOKB	M6 x 50	20	5	870
08HOOKB	M8 x 60	14	5	870

TYPE - BAG SUB TYPE - BAG30

### TIMPAC

06HOOKP	M6 x 50	2	10	-
08HOOKP	M8 x 60	2	10	-

TYPE - PAK SUB TYPE - PAK49

## Forged Hook Only

Yellow



CORROSION RATING



Clean, dry & low humidity environments

A useful threaded hook bolt for attaching ropes or cables. Manufactured using a forging process for extra strength preventing the hook from opening out when the load is applied.

Sold without shield anchor.

Product Code	Thread Ø x L (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-------------------	----------------	--------------------	--------------------

### BOX

06HOOK	M6 x 50	50	18	648
08HOOK	M8 x 60	50	10	300
10HOOK	M10 x 73	50	6	216
12HOOK	M12 x 90	25	8	240

TYPE - SHA SUB TYPE - SHA01

## Chemical Anchor Studs

Hot Dipped Galvanised

Zinc



CONCRETE BRICK STONE

HDG

CORROSION RATING



Urban & industrial areas with a moderate salt atmosphere

Zinc

CORROSION RATING



Clean, dry & low humidity environments

Designed for use when fixing with chemical resins.

- Chisel point, prevents the rod turning when tightening
- External hex drive
- Embedment depth mark
- Zinc plated and passivated or galvanised
- Grade 5.8

### Technical Data

Size Ø (mm)	M8	M10	M12	M16	M20
Drill Hole Ø (mm)	10	12	14	18	24
Fixture Clearance Hole Ø (mm)	10	12	14	18	24

Product Code	Size (mm)	MFT (mm)	Min. ED (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	----------	--------------	----------------	--------------------	--------------------

### BOX (NUT SETTER INCLUDED)

#### Hot Dipped Galvanised

08110CSG	M8 x 110	13	80	10	30	300
10130CSG	M10 x 130	20	90	10	20	200
12160CSG	M12 x 160	25	110	10	10	100
16190CSG	M16 x 190	35	125	10	8	80
20270CSG	M20 x 270	55	170	4	9	36

TYPE - CHZ SUB TYPE - CHZ01

#### Zinc

08110CS	M8 x 110	13	80	10	30	300
10130CS	M10 x 130	20	90	10	20	200
12160CS	M12 x 160	25	110	10	10	100
16190CS	M16 x 190	35	125	10	8	80
20270CS	M20 x 270	55	170	4	9	36

TYPE - CHZ SUB TYPE - CHZ01

#### TIMPAC

#### Zinc

08110CSP	M8 x 110	13	80	2	10	-
10130CSP	M10 x 130	20	90	2	10	-
12160CSP	M12 x 160	25	110	2	10	-

TYPE - PAK SUB TYPE - PAK50

MFT = Max Fixture Thickness. Min. ED = Min. Embedment Depth

## Threaded Bar

Grade 4.8 & 8.8 available in zinc.

Stainless steel also available.

See pages 59 & 66