


2 Part Styrene Free Wood Filler



Metolux 2 Part Styrene Free Wood Filler is a two component high strength polyester wood filler. It provides a strong high quality repair to wood imperfections.

Supplied in pre-coloured blends to match your wood type. The weatherproof formulation is ideal for internal and external applications with additives to help flex with the natural movement of timber

- Professional grade
- Easy to mix
- Easy to sand
- Can be painted, stained, varnished and waxed
- Non slump



Product Code	Size	Colour	Pack Qty (pcs)	Carton Qty (packs)
TIN				
65431	275ml	White	1	6
65432	770ml	White	1	6
65433	3.3L	White	1	2
65437	275ml	Pine	1	6
65438	770ml	Pine	1	6
65439	3.3L	Pine	1	2
65440	275ml	Light Oak	1	6
65441	770ml	Light Oak	1	6
65442	3.3L	Light Oak	1	2
65434	275ml	Dark Teak	1	6
65435	770ml	Dark Teak	1	6
65443	275ml	Light Redwood	1	6
65444	770ml	Light Redwood	1	6
65446	275ml	Dark Mahogany	1	6
65447	770ml	Dark Mahogany	1	6
TYPE - MFL SUB TYPE - MFL01				

2 Part Decor All Purpose Filler



Metolux 2 Part Universal Decor Filler is a fast hardening two component polyester filling paste for the repairing of holes and surface imperfections in a wide range of materials including wood, metal, concrete, plaster and fibreglass.

- Features:
- Easy to sand after 20 minutes
- Easy to blend



Product Code	Size	Colour	Pack Qty (pcs)	Carton Qty (packs)
TIN				
65425	500g	Light Grey	1	6
65427	1.5kg	Light Grey	1	6
65428	6.0kg	Light Grey	1	2
TYPE - MFL SUB TYPE - MFL01				

Metolux Hardener



Spare hardener for use with:
2 Part Styrene Free Wood Filler
2 Part Decor All Purpose Filler

Product Code	Size	Pack Qty (pcs)	Carton Qty (packs)
TUBE			
78792P	40g	2	10
TYPE - MFL SUB TYPE - MFL01			

2 Part Metoset Liquid Mortar



Metolux 2 Part Liquid is a two component polyester liquid mortar for crack and chip repair. Alternatively it can be used to fix threaded rod or rebar into concrete, stone or plain brick. Ideal for filling cracks and cavities in difficult to reach areas.

- Easy to apply
- Rapid setting
- Internal & external use
- Paintable
- Useful to fill cavities, cracks or difficult access areas
- High mechanical and physical resistance



Product Code	Size	Colour	Pack Qty (pcs)	Carton Qty (packs)
TIN				
65628	1.0kg	Grey	1	6
65627	5.0kg	Grey	1	2
TYPE - MFL SUB TYPE - MFL01				

Metobond 1-1 Epoxy Building Adhesive



General Purpose Epoxy Building Adhesive, Metolux Metobond has a thixotropic mixed consistency. It is designed predominantly for vertical and overhead applications and is offered as an extremely powerful structural adhesive with high chemical resistance.

Suitable for use with Concrete materials, Brick & Mortar or Stone, Ceramic, Tile or Glass elements, Iron, Aluminium, Copper, Marble, Wooden structures, adhesive or repair applications, bedding in (eg floor tiles), gap & crack filling in voids, grouting. Ideal for horizontal (overhead) or vertical use.

- Ready to use
- Easy to apply (thixotropic)
- Suitable for use in damp conditions
- High level of chemical resistance
- Non shrink epoxy
- Easy to pigment
- Re-usable unit
- Excellent structural characteristics
- Adheres to almost any surface
- Superior sealant qualities
- Cures down to 5°C

Product Code	Size	Colour	Pack Qty (pcs)	Carton Qty (packs)
TUB				
65379	10.0kg	Light Grey	1	10
TYPE - MFL SUB TYPE - MFL01				