

Exterior Gate & Door Hinges



Light Tee Hinge



Ideal for lightweight low use gates, sheds and animal hutches.

CORROSION RATING

Zinc				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Technical Data					
Band Length (mm)	100	150	200	250	300
Band Thickness (mm)	1.5	1.5	1.5	1.5	1.5
Knuckle Ø (mm)	7.5	7.5	7.5	7.5	7.5
Leaf Size L x W (mm)	72 x 20	72 x 20	80 x 20	80 x 20	90 x 20
To Suit Gate Width (mm)	200 - 300	300 - 450	400 - 600	500 - 750	600 - 900
Max. Gate Weight (kg)	5	5	10	10	10
No. of Screw Holes (Pair)	12	14	14	14	14
Screw Ø (mm)	3.5	3.5	3.5	3.5	3.5

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc				
BAG					
LTH4BB	LTH4ZB	100	4	1 Pair	200 Pairs
LTH6BB	LTH6ZB	150	6	1 Pair	120 Pairs
LTH8BB	LTH8ZB	200	8	1 Pair	100 Pairs
LTH10BB	LTH10ZB	250	10	1 Pair	100 Pairs
442268	442214	300	12	1 Pair	50 Pairs
TYPE - HGB		SUB TYPE - HGB01			
TIMBAG - FIXINGS INCLUDED					
LTH4B	LTH4Z	100	4	1 Pair	10 Pairs
LTH6B	LTH6Z	150	6	1 Pair	10 Pairs
LTH8B	LTH8Z	200	8	1 Pair	10 Pairs
LTH10B	LTH10Z	250	10	1 Pair	10 Pairs
LTH12B	LTH12Z	300	12	1 Pair	10 Pairs
TYPE - HGP		SUB TYPE - HGP01			

Medium Tee Hinge



Ideal for medium weight regular use gates, shed and garage doors in domestic applications.

CORROSION RATING

Epoxy Black	Zinc
1	2

Occasionally damp/wet rural and sheltered areas

CORROSION RATING

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data						
Band Length (mm)	250	300	350	375	400	450
Band Thickness (mm)	1.8	2.0	2.0	2.0	2.2	2.2
Knuckle Ø (mm)	8.5	9.5	9.5	9.5	11.5	11.5
Leaf Size L x W (mm)	90 x 25	100 x 25	115 x 25	115 x 25	128 x 30	140 x 30
To Suit Gate Width (mm)	500 - 750	600 - 900	700 - 1050	750 - 1125	800 - 1200	900 - 1350
Max. Gate Weight (kg)	30	30	30	40	40	40
No. of Screw Holes (Pair)	14	14	14	16	18	18
Screw Ø (mm)	4.0	4.0	4.0	4.0	5.0	5.0

Strong Tee Hinge



Ideal for heavy weight high use gates, sheds and garage doors in domestic applications.

CORROSION RATING

Epoxy Black				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

CORROSION RATING

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data						
Band Length (mm)	250	300	350	400	450	600
Band Thickness (mm)	2.3	2.3	2.3	2.8	2.8	2.8
Knuckle Ø (mm)	12.0	12.0	12.0	14.0	14.0	14.0
Leaf Size L x W (mm)	100 x 20	115 x 30	127 x 30	140 x 30	150 x 30	166 x 40
To Suit Gate Width (mm)	500 - 750	600 - 900	700 - 1050	800 - 1200	900 - 1350	1200 - 1800
Max. Gate Weight (kg)	40	40	60	60	80	80
No. of Screw Holes (Pair)	14	18	18	18	18	20
Screw Ø (mm)	4.0	4.0	4.0	4.0	5.0	5.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised			
BAG					
MTH10BB	MTH10ZB	MTH10GB	250	10	1 Pair 40 Pairs
MTH12BB	MTH12ZB	MTH12GB	300	12	1 Pair 40 Pairs
MTH14BB	MTH14ZB	MTH14GB	350	14	1 Pair 30 Pairs
MTH15BB	MTH15ZB	MTH15GB	375	15	1 Pair 30 Pairs
MTH16BB	MTH16ZB	MTH16GB	400	16	1 Pair 20 Pairs
MTH18BB	MTH18ZB	MTH18GB	450	18	1 Pair 20 Pairs
TYPE - HGB		SUB TYPE - HGB02			
TIMBAG - FIXINGS INCLUDED					
MTH10B	MTH10Z	MTH10G	250	10	1 Pair 10 Pairs
MTH12B	MTH12Z	MTH12G	300	12	1 Pair 10 Pairs
MTH14B	MTH14Z	MTH14G	350	14	1 Pair 8 Pairs
MTH15B	MTH15Z	MTH15G	375	15	1 Pair 10 Pairs
MTH16B	MTH16Z	MTH16G	400	16	1 Pair 8 Pairs
MTH18B	MTH18Z	MTH18G	450	18	1 Pair 6 Pairs
TYPE - HGP		SUB TYPE - HGP02			

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised				
BAG					
STH10BB	STH10GB	250	10	1 Pair	40 Pairs
STH12BB	STH12GB	300	12	1 Pair	30 Pairs
STH14BB	STH14GB	350	14	1 Pair	20 Pairs
STH16BB	STH16GB	400	16	1 Pair	20 Pairs
STH18BB	STH18GB	450	18	1 Pair	10 Pairs
STH24BB	STH24GB	600	24	1 Pair	10 Pairs
TYPE - HGB		SUB TYPE - HGB03			
TIMBAG - FIXINGS INCLUDED					
STH10B	STH10G	250	10	1 Pair	40 Pairs
STH12B	STH12G	300	12	1 Pair	30 Pairs
STH14B	STH14G	350	14	1 Pair	20 Pairs
STH16B	STH16G	400	16	1 Pair	20 Pairs
STH18B	STH18G	450	18	1 Pair	10 Pairs
STH24B	STH24G	600	24	1 Pair	10 Pairs
TYPE - HGP		SUB TYPE - HGP03			