

Heavy Reversible Hinge



Heavy reversible hinges are ideal for flush mounted heavy gates, garage and stable doors in domestic, commercial and agricultural applications. The pins of the hinges mount into the hinge cups and prevent gates or doors from being lifted off.

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.



CORROSION RATINGS

Epoxy Black				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data											
Band Length (mm)	250	300	350	400	450	500	600	750	900	1050	1200
Bend Thickness (mm)	4.8	4.8	4.8	4.8	4.8	4.8	5.6	5.6	5.6	5.6	5.6
Band Width (mm)	40	40	40	40	50	50	50	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	16	19	19	19	19
Pin Ø (inch)	1/2	1/2	1/2	1/2	5/8	5/8	5/8	3/4	3/4	3/4	3/4
To Suit Gate Width (mm)	500 - 750	600 - 900	700 - 1050	800 - 1200	900 - 1350	1000 - 1500	1200 - 1800	1500 - 2250	1800 - 2700	2100 - 3150	2400 - 3600
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	22	22	22	26	26	26	26	26	30	30	30
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised				
TIMBAG - FIXINGS INCLUDED					
HRH250B	HRH250G	250	10	1 Pair	5 Pairs
HRH300B	HRH300G	300	12	1 Pair	5 Pairs
HRH350B	HRH350G	350	14	1 Pair	5 Pairs
HRH400B	HRH400G	400	16	1 Pair	5 Pairs
HRH450B	HRH450G	450	18	1 Pair	5 Pairs
HRH500B	HRH500G	500	20	1 Pair	5 Pairs

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised				
TIMBAG - FIXINGS INCLUDED					
HRH600B	HRH600G	600	24	1 Pair	5 Pairs
HRH750B	HRH750G	750	30	1 Pair	5 Pairs
HRH900B	HRH900G	900	36	1 Pair	5 Pairs
HRH1050B	HRH1050G	1050	42	1 Pair	2 Pairs
HRH1200B	HRH1200G	1200	48	1 Pair	2 Pairs
TYPE - FGP					
SUB TYPE - FGP02					

Adjustable Band & Hook on Plate



Adjustable hook and band hinges are for hanging doors or gates flush with the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic, commercial and agricultural applications. They feature an adjustable eye bolt to allow for gate alignment whilst being fitted or at a later stage if any movement occurs.

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

CORROSION RATINGS

Epoxy Black				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data						
Band Length (mm)	350	450	600	750	900	1200
Bend Thickness (mm)	5.0	5.0	5.0	5.0	5.0	5.0
Bend Width (mm)	50	50	50	60	60	70
Pin Ø (mm)	19	19	19	19	19	19
Pin Ø (inch)	3/4	3/4	3/4	3/4	3/4	3/4
Hook Plate L x W (mm)	160 x 50	160 x 50	200 x 60	200 x 60	200 x 60	200 x 60
To Suit Gate Width (mm)	700 - 1050	900 - 1350	1200 - 1800	1500 - 2250	1800 - 2700	2400 - 3600
No. of Bolt Holes (Pair)	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	14	14	14	18	20
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised				
TIMBAG - FIXINGS INCLUDED					
ABH350B	ABH350G	350	14	1 Pair	4 Pairs
ABH450B	ABH450G	450	18	1 Pair	4 Pairs
ABH600B	ABH600G	600	24	1 Pair	4 Pairs
ABH750B	ABH750G	750	30	1 Pair	4 Pairs
ABH900B	ABH900G	900	36	1 Pair	4 Pairs
ABH1200B	ABH1200G	1200	48	1 Pair	2 Pairs
TYPE - FGH					
SUB TYPE - FGH02					