

Straight Band & Hook on Plate



Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

The straight pattern hook and band hinges are for hanging the door or gate in front of the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic and agricultural applications. Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.



CORROSION RATINGS

Epoxy Black				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data									
Band Length (mm)	250	300	350	400	450	500	600	750	900
Band Thickness (mm)	4.8	4.8	4.8	4.8	4.8	4.8	5.4	5.4	5.4
Band Width (mm)	40	40	40	40	50	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	16	19	19
Pin Ø (inch)	1/2	1/2	1/2	1/2	5/8	5/8	5/8	3/4	3/4
Hook Plate L x W (mm)	115 x 40	115 x 40	115 x 40	115 x 40	160 x 50	160 x 50	160 x 50	200 x 75	200 x 75
To Suit Gate Width (mm)	500 - 750	600 - 900	700 - 1050	800 - 1200	900 - 1350	1000 - 1500	1200 - 1800	1500 - 2250	1800 - 2700
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	12	12	14	14	14	14	14	16
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised	TIMBAG - FIXINGS INCLUDED			
HBS250B	HBS250G	250	10	1 Pair	5 Pairs
HBS300B	HBS300G	300	12	1 Pair	5 Pairs
HBS350B	HBS350G	350	14	1 Pair	5 Pairs
HBS400B	HBS400G	400	16	1 Pair	5 Pairs
HBS450B	HBS450G	450	18	1 Pair	5 Pairs

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised	TIMBAG - FIXINGS INCLUDED			
HBS500B	HBS500G	500	20	1 Pair	5 Pairs
HBS600B	HBS600G	600	24	1 Pair	5 Pairs
HBS750B	HBS750G	750	30	1 Pair	5 Pairs
HBS900B	HBS900G	900	36	1 Pair	5 Pairs
TYPE - FGH		SUB TYPE - FGH03			

Cranked Band & Hook on Plate



Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

The cranked pattern hook and band hinges are for hanging the door or gate flush with the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic and agricultural applications. Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.



CORROSION RATINGS

Epoxy Black				
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data									
Band Length (mm)	250	300	350	400	450	500	600	750	900
Band Thickness (mm)	4.8	4.8	4.8	4.8	4.8	4.8	5.4	5.4	5.4
Band Width (mm)	40	40	40	40	50	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	16	19	19
Pin Ø (inch)	1/2	1/2	1/2	1/2	5/8	5/8	5/8	3/4	3/4
Hook Plate L x W (mm)	115 x 40	115 x 40	115 x 40	115 x 40	160 x 50	160 x 50	160 x 50	200 x 75	200 x 75
To Suit Gate Width (mm)	500 - 750	600 - 900	700 - 1050	800 - 1200	900 - 1350	1000 - 1500	1200 - 1800	1500 - 2250	1800 - 2700
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	12	12	14	14	14	14	14	16
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised	TIMBAG - FIXINGS INCLUDED			
HBC250B	HBC250G	250	10	1 Pair	5 Pairs
HBC300B	HBC300G	300	12	1 Pair	5 Pairs
HBC350B	HBC350G	350	14	1 Pair	5 Pairs
HBC400B	HBC400G	400	16	1 Pair	5 Pairs
HBC450B	HBC450G	450	18	1 Pair	5 Pairs

Product Code		Band Length (mm)	Band Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised	TIMBAG - FIXINGS INCLUDED			
HBC500B	HBC500G	500	20	1 Pair	5 Pairs
HBC600B	HBC600G	600	24	1 Pair	5 Pairs
HBC750B	HBC750G	750	30	1 Pair	5 Pairs
HBC900B	HBC900G	900	36	1 Pair	5 Pairs
TYPE - FGH		SUB TYPE - FGH02			