


Oval Padbolt



Oval padbolts are ideal for securing flush fitting narrow stile gates and doors in domestic and light commercial applications. They are padlockable and fixed with carriage bolts for added security.

CORROSION RATINGS

Epoxy Black		Zinc		
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data	
Bolt Length (mm)	100
Bolt Ø (mm)	12
Bolt Throw (mm)	40
Plate Size L x W (mm)	55 x 100
Staple Keep Size L x W (mm)	73 x 24
Max. Padlock Shackle Ø (mm)	10
No. of Carriage Bolt Holes	10
Carriage Bolt Ø (mm)	4.0

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS						
OP4BB	OP4ZB	OP4GB	100	4	1	10
TYPE - BTB					SUB TYPE - BTB03	
TIMBAG - FIXINGS INCLUDED						
OP4BP	OP4ZP	OP4GP	100	4	1	10
TYPE - BTP					SUB TYPE - BTP03	

Slide Action Padbolt



CORROSION RATING

Epoxy Black		Zinc		
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Slide action padbolts are ideal for securing flush fitting gates and doors in domestic and light commercial applications when the bolt is exposed externally. They are padlockable and fixed with eight carriage bolts to prevent the bolt being wrenched from the door.

Technical Data	
Bolt Length (mm)	185
Bolt Ø (mm)	9
Bolt Throw (mm)	60
Plate Size L x W (mm)	105 x 72
Staple Keep Size L x W (mm)	76 x 25
Max. Padlock Shackle Ø (mm)	8
No. of Carriage Bolt Holes	8
Carriage Bolt Ø (mm)	M6

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS						
282456	282789		185	7.2	1	80
TYPE - BTB					SUB TYPE - BTB04	
TIMBAG - FIXINGS INCLUDED						
287114	287585		185	7.2	1	10
TYPE - BTP					SUB TYPE - BTP04	

Necked Tower Bolt



Necked tower bolts are used for securing recessed fitting gates and shed doors in a closed position.

CORROSION RATINGS

Epoxy Black		Zinc		
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data			
Bolt Length (mm)	100	150	200
Bolt Ø (mm)	10	10	11
Bolt Throw (mm)	40	40	50
Plate Size L x W (mm)	118 x 38	165 x 38	225 x 45
Flat Keep Size L x W (mm)	43 x 27	43 x 27	43 x 27
Flat Keep Hole Size (mm)	12	12	12
No. of Screw Holes	8	10	10
Screw Ø (mm)	4.0	4.0	4.0

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
BAG - EXCLUDES FIXINGS						
TBN4BB	TBN4GB		100	4	1	15
TBN6BB	TBN6GB		150	6	1	15
TBN8BB	TBN8GB		200	8	1	15
TYPE - BTB					SUB TYPE - BTB02	
TIMBAG - FIXINGS INCLUDED						
TBN4BP	TBN4GP		100	4	1	15
TBN6BP	TBN6GP		150	6	1	15
TBN8BP	TBN8GP		200	8	1	15
TYPE - BTP					SUB TYPE - BTP02	

Straight Tower Bolt



Straight tower bolts are used for securing flush fitting gates and shed doors in a closed position.

CORROSION RATINGS

Epoxy Black		Zinc		
1	2	3	4	5

Occasionally damp/wet rural and sheltered areas

Hot Dipped Galvanised				
1	2	3	4	5

Urban & industrial areas with a moderate salt atmosphere

Technical Data					
Bolt Length (mm)	75	100	150	200	250
Bolt Ø (mm)	10	10	10	10	10
Bolt Throw (mm)	20	25	25	35	35
Plate Size L x W (mm)	95 x 38	118 x 38	165 x 38	225 x 45	276 x 45
Staple Keep Size L x W (mm)	39 x 25	39 x 25	46 x 33	46 x 33	46 x 33
No. of Screw Holes	6	8	10	10	10
Screw Ø (mm)	4.0	4.0	4.0	4.0	4.0

Product Code			Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Zinc	Hot Dipped Galvanised				
BAG - EXCLUDES FIXINGS						
TBS3BB	TBS3ZB	TBS3GB	75	3	1	100
TBS4BB	TBS4ZB	TBS4GB	100	4	1	120
TBS6BB	TBS6ZB	TBS6GB	150	6	1	100
TBS8BB	TBS8ZB	TBS8GB	200	8	1	40
TBS10BB	TBS10ZB	TBS10GB	250	10	1	40
TYPE - BTB					SUB TYPE - BTB02	
TIMBAG - FIXINGS INCLUDED						
TBS3BP	TBS3ZP	TBS3GP	75	3	1	15
TBS4BP	TBS4ZP	TBS4GP	100	4	1	15
TBS6BP	TBS6ZP	TBS6GP	150	6	1	15
TBS8BP	TBS8ZP	TBS8GP	200	8	1	15
TBS10BP	TBS10ZP	TBS10GP	250	10	1	15
TYPE - BTP					SUB TYPE - BTP02	