rimeo

Field Gate Hinge Sets

Standard Double Strap Hinge Set



Ideal for use on field gates and driveway gates that are to be hung on timber posts. The hinge set provides exceptional support to the gate as the top band and bottom strap wrap around the gate and are fixed with cup square bolts to firmly secure in place.

The hook to bolt features a 9mm drilled hole for R clips or linch pins (not included) to be fitted to prevent the gate being lifted off. The hooks to drive are barbed to prevent the gate from working loose.

Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.

1 x Top Strap 1 x Bottom Strap 1 x Hook to Drive 1 x Hook to Bolt M10x95mm Galvanised Cup Square Bolts M10 Hex Nuts & Washers 6.0x40mm Exterior Woodscrews

Contents:

Field Gate Information						
To Suit Gate Width		3 - 4ft / 900 - 1200mm	4 - 9ft / 1200 - 2700mm	9 - 12ft / 2700 - 3600mm		
To Suit Gate Thickness		3" / 75mm	3" / 75mm	3" / 75mm		
Product Dimensions						
Top Strap Length	(TSL)	12" / 300mm	18" / 450mm	24" / 600mm		
Bottom Strap Length	(BSL)	6" / 150mm	6" / 150mm	6" / 150mm		
Hook To Bolt Ø x Length (mm)		M20 x 350	M20 x 350	M20 x 350		
Hook To Drive Length (mm)		215	215	215		
PinØ		3/4" / 19mm	3/4" / 19mm	3/4" / 19mm		
Fixings Information						
No. of Carriage Bolts		3	4	4		
Carriage Bolt Ø (mm)		M10	M10	M10		

Product Code	Top Strap	Top Strap	To Suit	To Suit	Pack	Carton	
Hot Dipped Galvanised	Length (inch)	Length (mm)	Gate Width (ft)	Gate Width (mm)	Qty (pcs)	Qty (packs)	
BAG - FIXINGS INCLUDED							
SFH300G	12	300	3 - 4	900 - 1200	1	4	
SFH450G	18	450	4 - 9	1200 - 2700	1	4	
SFH600G	24	600	9 - 12	2700 - 3600	1	4	
TYPE - FGS SUB TYPE - FGS01					E - FGS01		

Double Strap Hinge Set with Hook on Plate



Ideal for use on field gates and driveway gates that are to be hung on timber, concrete or masonry posts.

The hinge set provides exceptional support to the gate as the top band and bottom strap wrap around the gate and are fixed with cup square bolts to firmly secure in place.

Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.

Contents: 1 x Top Strap 1 x Bottom Strap 2 x Hook on Plates M10x95mm Galvanised Cup Square Bolts M10 Hex Nuts & Washers M10x65mm Galv Coach Screws 6.0x40mm Exterior Woodscrews.

Field Gate Information						
To Suit Gate Width	3 - 4ft / 900 - 1200mm	4 - 9ft / 1200 - 2700mm	9 - 12ft / 2700 - 3600mm			
To Suit Gate Thickness	3" / 75mm	3" / 75mm	3" / 75mm			
Product Dimensions						
Top Strap Length (TSL)	12" / 300mm	18" / 450mm	24" / 600mm			
Bottom Strap Length (BSL)	6" / 150mm	6" / 150mm	6" / 150mm			
Hook on Plate Length x Width (mm)	100 x 100	100 x 100	100 x 100			
PinØ	3/4" / 19mm	3/4" / 19mm	3/4" / 19mm			
Fixings Information						
No. of Coach Screws	8	8	8			
Coach Screws Ø (mm)	M10	M10	M10			
No. of Carriage Bolts	3	4	4			
Carriage Bolt Ø (mm)	M10	M10	M10			

Product Code	Top Strap Length (inch)	Top Strap To Suit	To Suit	Pack	Carton	
Hot Dipped Galvanised		Length (mm)	Gate Width (ft)	Gate Width (mm)	Qty (pcs)	Qty (packs)
BAG - FIXINGS INCLUDED						
DSFH300G	12	300	3 - 4	900 - 1200	1	4
DSFH450G	18	450	4 - 9	1200 - 2700	1	4
DSFH600G	24	600	9 - 12	2700 - 3600	1	4
TYPE - FGS SUB TYPE - FGS01						E - FGS01