

Throw-Over Loops



Throw-Over Gate Loop



CORROSION RATING

Hot Dipped Galvanised

1	2	3	4	5
---	---	---	---	---

Urban & industrial areas with a moderate salt atmosphere

Ideal for securing pairs of gates in a closed position.

Product Code	Length (mm)	Thickness (mm)	To Suit Gate Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised					
BAG - FIXINGS INCLUDED					
TGL150G	150	6	75	1	10
TGL350G	350	6	75	1	10
TYPE - FGH			SUB TYPE - FGH01		

Throw-Over Gate Loop with Lifting Handle



CORROSION RATING

Hot Dipped Galvanised

1	2	3	4	5
---	---	---	---	---

Urban & industrial areas with a moderate salt atmosphere

Ideal for securing pairs of gates in a closed position. Features a loop handle for ease of operation, particularly from the saddle of a horse.

Product Code	Length (mm)	Thickness (mm)	To Suit Gate Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised					
BAG - NO FIXINGS REQUIRED					
TGLH350G	350	6	75	1	10
TGLH450G	450	6	75	1	10
TYPE - FGH			SUB TYPE - FGH01		

Throw-Over Locking Gate Loop



CORROSION RATING

Hot Dipped Galvanised

1	2	3	4	5
---	---	---	---	---

Urban & industrial areas with a moderate salt atmosphere

Ideal for securing pairs of gates in a closed position. Features a locking hasp and staple to prevent risk of animal / equipment theft or unwanted access.

Product Code	Length (mm)	Thickness (mm)	Staple Plate Size (mm)	To Suit Gate Thickness (mm)	Max. Padlock Shackle Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised							
BAG - NO FIXINGS REQUIRED							
TLGL450G	450	6	65 x 65	75	12	1	10
TYPE - FGH			SUB TYPE - FGH01				

Field Gate Wheels



Light Duty Spring Loaded Field Gate Wheel



CORROSION RATING

Zinc

1	2	3	4	5
---	---	---	---	---

Occasionally damp/wet rural and sheltered areas

Technical Data	
Length (mm)	270
Wheel Diameter Ø (mm)	100
Backplate Length x Width (mm)	100 x 25
Max. Gate Weight (kg)	50
Max. Spring Compression (mm)	40

A light duty spring loaded gate wheel that is ideal for domestic and light commercial applications. Provides support at the leading edge of gates and doors and self adjusts to overcome sloping or uneven groundwork.

Product Code	Length (mm)	Pack Qty (pcs)	Carton Qty (packs)
Zinc			
PLAIN BAG - FIXINGS INCLUDED			
GW10ZB	270	1	10
TYPE - GAB		SUB TYPE - GAB06	

Heavy Duty Spring Loaded Field Gate Wheel



CORROSION RATING

Epoxy Black

1	2	3	4	5
---	---	---	---	---

Occasionally damp/wet rural and sheltered areas

Technical Data	
Length (mm)	370
Wheel Diameter Ø (mm)	102
Backplate Length x Width (mm)	165 x 50
Max. Gate Weight (kg)	135
Max. Spring Compression (mm)	50

A heavy duty spring loaded gate wheel that is ideal for agricultural and heavy commercial applications. This wheel provides support at the leading edge of gates and doors and self adjusts to overcome sloping or uneven groundwork.

Product Code	Length (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black			
PLAIN BAG - FIXINGS INCLUDED			
GW14BB	370	1	5
TYPE - GAB		SUB TYPE - GAB06	