

Declaration of Performance

No. DOP-01-CLA-04 / Page 1 of 7

Classic Multi-Purpose Screws



Material - Stainless Steel A2 (SUS-302)

Head Type - Double Countersunk

Screw Diameter (mm) - 3.0, 3.5, 4.0, 4.5, 5.0, 6.0

We hereby declare these designated products have performed initial type testing under system 3, Annex V of the regulation (EU) no. 305/2011 (Construction Products Regulation), with the reference to the harmonised European standard (hEN) BS EN 14592:2008+A1:2012 (Timber structures - Dowel type fasteners - Requirements) for screws intended for the use in "load bearing timber structures" and produced the calculation/test reports as attached;

The initial type testing has been carried out by independent notified body;
Strojirensky Zkusebni Ustav, NB # 1015, Hudcova 424/56B, 621 00 Brno-Medlánky, Czechia

Certificate Number: E-30-20002-13 to E-30-20007-13

Test Report Number: No. 30-9797/1 to No. 30-9797/6

Factory Process Control (FPC) has been established by the factory and independently audited by TUV Rheinland UK in accordance with ISO9001.

This declaration of conformity is valid until there is a significant change in the product and declared characteristics. ie. raw material or change in production process.

This declaration is the responsibility of the importer ; T.I.Midwood & Co. Ltd.

Simon Midwood

Managing Director

TIMCO House
2012

2012

Name

Position

Signature

Location & Date

Test Year

Declaration of Performance

No. DOP-01-CLA-04 / Page 2 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø3.0mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	3.0
Head diameter (mm)	6.0
Inner thread diameter (mm)	2.00

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 20° [Nmm] (thread section) in acc. to EN 409	1089
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	20.14
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	12.96
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 375\text{kg/m}^3$	38.56
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	2.27
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	2.01

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance

No. DOP-01-CLA-04 / Page 3 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø3.5mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	3.5
Head diameter (mm)	7.0
Inner thread diameter (mm)	2.25

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 18° [Nmm] (thread section) in acc. to EN 409	1640
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	17.80
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	11.58
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm²] in acc. to EN 1383 with density of wood $\rho_k = 375\text{kg/m}^3$	27.12
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	2.80
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	1.81

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance

No. DOP-01-CLA-04 / Page 4 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø4.0mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	4.0
Head diameter (mm)	8.0
Inner thread diameter (mm)	2.50

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 17° [Nmm] (thread section) in acc. to EN 409	2129
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	18.62
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 390\text{kg/m}^3$	10.23
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 370\text{kg/m}^3$	24.59
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	3.38
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	1.25

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance

No. DOP-01-CLA-04 / Page 5 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø4.5mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	4.5
Head diameter (mm)	9.0
Inner thread diameter (mm)	2.70

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 15° [Nmm] (thread section) in acc. to EN 409	3065
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 420\text{kg/m}^3$	20.97
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 420\text{kg/m}^3$	11.86
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 390\text{kg/m}^3$	20.56
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	4.13
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	1.24

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance

No. DOP-01-CLA-04 / Page 6 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø5.0mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	5.0
Head diameter (mm)	10.0
Inner thread diameter (mm)	3.10

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 14° [Nmm] (thread section) in acc. to EN 409	4217
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 410\text{kg/m}^3$	20.92
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 410\text{kg/m}^3$	14.08
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 420\text{kg/m}^3$	22.08
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	5.07
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	1.23

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance

No. DOP-01-CLA-04 / Page 7 of 7

Classic Multi-Purpose Screws Double Countersunk Head - Ø6.0mm

Material & Geometry

Material	Stainless Steel A2 (SUS-302)
Screw diameter (mm)	6.0
Head diameter (mm)	12.0
Inner thread diameter (mm)	3.80

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 12° [Nmm] (thread section) in acc. to EN 409	6629
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 420\text{kg/m}^3$	18.63
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 420\text{kg/m}^3$	13.05
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 465\text{kg/m}^3$	26.90
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	5.72
Characteristic torsional ratio in acc. to EN 15737 with density of wood $\rho_k = 450\text{kg/m}^3$	1.14

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1